

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
T16	G5	14	827	≥ 80	-	1200	549	FDH-14/27/1B-L/P-G5-16/549	-	86
T16	G5	14	830	≥ 80	-	1200	549	FDH-14/30/1B-L/P-G5-16/549	-	86
T16	G5	14	840	≥ 80	-	1200	549	FDH-14/40/1B-L/P-G5-16/549	-	86
T16	G5	14	865	≥ 80	-	1100	549	FDH-14/65/1B-L/P-G5-16/549	-	79
T16	G5	24	827	≥ 80	-	1750	549	FDH-24/27/1B-L/P-G5-16/549	-	73
T16	G5	24	830	≥ 80	-	1750	549	FDH-24/30/1B-L/P-G5-16/549	-	73
T16	G5	24	840	≥ 80	-	1750	549	FDH-24/40/1B-L/P-G5-16/549	-	73
T16	G5	24	865	≥ 80	-	1600	549	FDH-24/65/1B-L/P-G5-16/549	-	67
T16	G5	24	940	≥ 90	-	1400	549	FDH-24/40/1A-L/P-G5-16/549	-	58
T16	G5	24	965	≥ 90	-	1300	549	FDH-24/65/1A-L/P-G5-16/549	-	54
T16	G5	21	827	≥ 80	-	1900	849	FDH-21/27/1B-L/P-G5-16/849	-	90
T16	G5	21	830	≥ 80	-	1900	849	FDH-21/30/1B-L/P-G5-16/849	-	90

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
T16	G5	21	840	≥ 80	-	1900	849	FDH-21/40/1B-L/P-G5-16/849	-	90
T16	G5	21	865	≥ 80	-	1750	849	FDH-21/65/1B-L/P-G5-16/849	-	83
T16	G5	39	827	≥ 80	-	3100	849	FDH-39/27/1B-L/P-G5-16/849	-	79
T16	G5	39	830	≥ 80	-	3100	849	FDH-39/30/1B-L/P-G5-16/849	-	79
T16	G5	39	840	≥ 80	-	3100	849	FDH-39/40/1B-L/P-G5-16/849	-	79
T16	G5	39	865	≥ 80	-	2850	849	FDH-39/65/1B-L/P-G5-16/849	-	73
T16	G5	28	827	≥ 80	-	2600	1149	FDH-28/27/1B-L/P-G5-16/1149	-	93
T16	G5	28	830	≥ 80	-	2600	1149	FDH-28/30/1B-L/P-G5-16/1149	-	93
T16	G5	28	840	≥ 80	-	2600	1149	FDH-28/40/1B-L/P-G5-16/1149	-	93
T16	G5	28	865	≥ 80	-	2400	1149	FDH-28/65/1B-L/P-G5-16/1149	-	86
T16	G5	54	827	≥ 80	-	4450	1149	FDH-54/27/1B-L/P-G5-16/1149	-	82
T16	G5	54	830	≥ 80	-	4450	1149	FDH-54/30/1B-L/P-G5-16/1149	-	82

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
T16	G5	54	840	≥ 80	-	4450	1149	FDH-54/40/1B-L/P-G5-16/1149	-	82
T16	G5	54	865	≥ 80	-	4050	1149	FDH-54/65/1B-L/P-G5-16/1149	-	75
T16	G5	54	940	≥ 90	-	3500	1149	FDH-54/40/1A-L/P-G5-16/1149	-	65
T16	G5	54	965	≥ 90	-	3450	1149	FDH-54/65/1A-L/P-G5-16/1149	-	64
T16	G5	35	827	≥ 80	-	3300	1449	FDH-35/27/1B-L/P-G5-16/1449	-	94
T16	G5	35	830	≥ 80	-	3300	1449	FDH-35/30/1B-L/P-G5-16/1449	-	94
T16	G5	35	840	≥ 80	-	3300	1449	FDH-35/40/1B-L/P-G5-16/1449	-	94
T16	G5	35	865	≥ 80	-	3050	1449	FDH-35/65/1B-L/P-G5-16/1449	-	87
T16	G5	49	827	≥ 80	-	4300	1449	FDH-49/27/1B-L/P-G5-16/1449	-	88
T16	G5	49	830	≥ 80	-	4300	1449	FDH-49/30/1B-L/P-G5-16/1449	-	88
T16	G5	49	840	≥ 80	-	4300	1449	FDH-49/40/1B-L/P-G5-16/1449	-	88
T16	G5	49	940	≥ 90	-	3500	1449	FDH-49/40/1A-L/P-G5-16/1449	-	71

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
T16	G5	49	965	≥ 90	-	3450	1449	FDH-49/65/1A-L/P-G5-16/1449	-	70
T16	G5	80	827	≥ 80	-	6150	1449	FDH-80/27/1B-L/P-G5-16/1449	-	77
T16	G5	80	830	≥ 80	-	6150	1449	FDH-80/30/1B-L/P-G5-16/1449	-	77
T16	G5	80	840	≥ 80	-	6150	1449	FDH-80/40/1B-L/P-G5-16/1449	-	77
T16	G5	80	860	≥ 80	-	5700	1449	FDH-80/60/1B-L/P-G5-16/1449	-	71
T26	G13	15	827	≥ 80	950	950	438	FD-15/27/1B-E-G13-26/438	63	63
T26	G13	15	830	≥ 80	950	950	438	FD-15/30/1B-E-G13-26/438	63	63
T26	G13	15	840	≥ 80	950	950	438	FD-15/40/1B-E-G13-26/438	63	63
T26	G13	15	930	≥ 90	650	700	438	FD-15/30/1A-E-G13-26/438	43	47
T26	G13	15	954	≥ 90	680	750	438	FD-15/54/1A-E-G13-26/438	45	50
T26	G13	18	827	≥ 80	1350	1300	590	FD-18/27/1B-E-G13-26/590	75	72
T26	G13	18	830	≥ 80	1350	1300	590	FD-18/30/1B-E-G13-26/590	75	72

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
T26	G13	18	840	≥ 80	1350	1300	590	FD-18/40/1B-E-G13-26/590	75	72
T26	G13	18	865	≥ 80	1300	1250	590	FD-18/65/1B-E-G13-26/590	72	69
T26	G13	18	930	≥ 90	900	850	590	FD-18/30/1A-E-G13-26/590	50	47
T26	G13	18	940	≥ 90	950	900	590	FD-18/40/1A-E-G13-26/590	53	50
T26	G13	18	954	≥ 90	1000	950	590	FD-18/54/1A-E-G13-26/590	56	53
T26	G13	18	965	≥ 90	1000	950	590	FD-18/65/1A-E-G13-26/590	56	53
T26	G13	36	827	≥ 80	3350	3200	1200	FD-36/27/1B-E-G13-26/1200	93	89
T26	G13	36	830	≥ 80	3350	3200	1200	FD-36/30/1B-E-G13-26/1200	93	89
T26	G13	36	840	≥ 80	3350	3200	1200	FD-36/40/1B-E-G13-26/1200	93	89
T26	G13	36	865	≥ 80	3250	3150	1200	FD-36/65/1B-E-G13-26/1200	90	88
T26	G13	36	930	≥ 90	2200	2100	1200	FD-36/30/1A-E-G13-26/1200	61	58
T26	G13	36	940	≥ 90	2250	2150	1200	FD-36/40/1A-E-G13-26/1200	63	60

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
T26	G13	36	954	≥ 90	2300	2200	1200	FD-36/54/1A-E-G13-26/1200	64	61
T26	G13	36	965	≥ 90	2300	2200	1200	FD-36/65/1A-E-G13-26/1200	64	61
T26	G13	58	827	≥ 80	5200	5000	1500	FD-58/27/1B-E-G13-26/1500	90	86
T26	G13	58	830	≥ 80	5200	5000	1500	FD-58/30/1B-E-G13-26/1500	90	86
T26	G13	58	840	≥ 80	5200	5000	1500	FD-58/40/1B-E-G13-26/1500	90	86
T26	G13	58	865	≥ 80	5000	4750	1500	FD-58/65/1B-E-G13-26/1500	86	82
T26	G13	58	930	≥ 90	3500	3400	1500	FD-58/30/1A-E-G13-26/1500	60	59
T26	G13	58	940	≥ 90	3600	3500	1500	FD-58/40/1A-E-G13-26/1500	62	60
T26	G13	58	954	≥ 90	3700	3600	1500	FD-58/54/1A-E-G13-26/1500	64	62
T26	G13	58	965	≥ 90	3700	3600	1500	FD-58/65/1A-E-G13-26/1500	64	62
T-R16	2GX13	22	827	≥ 80	-	1800	230	FC-22/27/1B-E-2GX13-16	-	82
T-R16	2GX13	22	830	≥ 80	-	1800	230	FC-22/30/1B-E-	-	82

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
								2GX13-16		
T-R16	2GX13	22	840	≥ 80	-	1800	230	FC-22/40/1B-E-2GX13-16	-	82
T-R16	2GX13	22	865	≥ 80	-	1700	230	FC-22/65/1B-E-2GX13-16	-	77
T-R16	2GX13	40	827	≥ 80	-	3200	305	FC-40/27/1B-E-2GX13-16	-	80
T-R16	2GX13	40	830	≥ 80	-	3200	305	FC-40/30/1B-E-2GX13-16	-	80
T-R16	2GX13	40	840	≥ 80	-	3200	305	FC-40/40/1B-E-2GX13-16	-	80
T-R16	2GX13	40	865	≥ 80	-	3000	305	FC-40/65/1B-E-2GX13-16	-	75
T-R16	2GX13	55	827	≥ 80	-	4200	305	FC-55/27/1B-E-2GX13-16	-	76
T-R16	2GX13	55	830	≥ 80	-	4200	305	FC-55/30/1B-E-2GX13-16	-	76
T-R16	2GX13	55	840	≥ 80	-	4200	305	FC-55/40/1B-E-2GX13-16	-	76
T-R16	2GX13	55	865	≥ 80	-	3800	305	FC-55/65/1B-	-	69

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
								E-2GX13-16		
TC-SEL	2G7	5	827	≥ 80	-	250	85	FSD-5/27/1B-E-2G7	-	50
TC-SEL	2G7	5	840	≥ 80	-	250	85	FSD-5/40/1B-E-2G7	-	50
TC-SEL	2G7	7	827	≥ 80	-	400	115	FSD-7/27/1B-E-2G7	-	57
TC-SEL	2G7	7	830	≥ 80	-	400	115	FSD-7/30/1B-E-2G7	-	57
TC-SEL	2G7	7	840	≥ 80	-	400	115	FSD-7/40/1B-E-2G7	-	57
TC-SEL	2G7	9	827	≥ 80	-	600	145	FSD-9/27/1B-E-2G7	-	67
TC-SEL	2G7	9	830	≥ 80	-	600	145	FSD-9/30/1B-E-2G7	-	67
TC-SEL	2G7	9	840	≥ 80	-	600	145	FSD-9/40/1B-E-2G7	-	67
TC-SEL	2G7	11	827	≥ 80	-	900	215	FSD-11/27/1B-E-2G7	-	82
TC-SEL	2G7	11	830	≥ 80	-	900	215	FSD-11/30/1B-E-2G7	-	82
TC-SEL	2G7	11	840	≥ 80	-	900	215	FSD-11/40/1B-E-2G7	-	82
TC-L	2G11	18	827	≥ 80	1200	1200	225	FSD-18/27/1B-E-2G11	67	67
TC-L	2G11	18	830	≥ 80	1200	1200	225	FSD-18/30/1B-E-2G11	67	67
TC-L	2G11	18	840	≥ 80	1200	1200	225	FSD-18/40/1B-E-2G11	67	67
TC-L	2G11	18	930	≥ 90	750	750	225	FSD-18/30/1A-2G11	42	42

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
TC-L	2G11	18	940	≥ 90	750	750	225	FSD-18/40/1A-2G11	42	42
TC-L	2G11	18	950	≥ 90	750	750	225	FSD-18/50/1A-2G11	42	42
TC-L	2G11	24	827	≥ 80	1800	1800	320	FSD-24/27/1B-E-2G11	75	75
TC-L	2G11	24	830	≥ 80	1800	1800	320	FSD-24/30/1B-E-2G11	75	75
TC-L	2G11	24	840	≥ 80	1800	1800	320	FSD-24/40/1B-E-2G11	75	75
TC-L	2G11	24	930	≥ 90	1200	1200	320	FSD-24/30/1A-2G11	50	50
TC-L	2G11	24	940	≥ 90	1200	1200	320	FSD-24/40/1A-2G11	50	50
TC-L	2G11	24	950	≥ 90	1200	1200	320	FSD-24/50/1A-2G11	50	50
TC-L	2G11	36	827	≥ 80	2900	2900	415	FSD-36/27/1B-E-2G11	81	81
TC-L	2G11	36	830	≥ 80	2900	2900	415	FSD-36/30/1B-E-2G11	81	81
TC-L	2G11	36	840	≥ 80	2900	2900	415	FSD-36/40/1B-E-2G11	81	81
TC-L	2G11	36	860	≥ 80	2750	2750	415	FSD-36/60/1B-E-2G11	76	76
TC-L	2G11	36	930	≥ 90	1900	1900	415	FSD-36/30/1A-2G11	53	53
TC-L	2G11	36	940	≥ 90	1900	1900	415	FSD-36/40/1A-2G11	53	53
TC-L	2G11	36	950	≥ 90	1900	1900	415	FSD-36/50/1A-2G11	53	53
TC-L	2G11	40	827	≥ 80	-	3500	535	FSDH-40/27/1B-2G11	-	88

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
TC-L	2G11	40	830	≥ 80	-	3500	535	FSDH-40/30/1B-2G11	-	88
TC-L	2G11	40	840	≥ 80	-	3500	535	FSDH-40/40/1B-2G11	-	88
TC-L	2G11	40	950	≥ 90	-	2200	535	FSDH-40/50/1A-2G11	-	55
TC-L	2G11	55	827	≥ 80	-	4800	535	FSDH-55/27/1B-2G11	-	87
TC-L	2G11	55	830	≥ 80	-	4800	535	FSDH-55/30/1B-2G11	-	87
TC-L	2G11	55	840	≥ 80	-	4800	535	FSDH-55/40/1B-2G11	-	87
TC-L	2G11	55	860	≥ 80	-	4550	535	FSDH-55/60/1B-2G11	-	83
TC-L	2G11	55	930	≥ 90	-	3000	535	FSDH-55/30/1A-2G11	-	55
TC-L	2G11	55	940	≥ 90	-	3000	535	FSDH-55/40/1A-2G11	-	55
TC-L	2G11	55	950	≥ 90	-	3000	535	FSDH-55/50/1A-2G11	-	55
TC-L	2G11	80	830	≥ 80	-	6000	565	FSDH-80/30/1B-2G11	-	75
TC-L	2G11	80	840	≥ 80	-	6000	565	FSDH-80/40/1B-2G11	-	75
TC-D	G24d-1	10	827	≥ 80	600	-	95	FSQ-10/27/1B-I-G24d=1	60	-
TC-D	G24d-1	10	830	≥ 80	600	-	95	FSQ-10/30/1B-I-G24d=1	60	-
TC-D	G24d-1	10	840	≥ 80	600	-	95	FSQ-10/40/1B-I-G24d=1	60	-
TC-D	G24d-1	13	827	≥ 80	900	-	130	FSQ-13/27/1B-I-G24d=1	69	-

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
TC-D	G24d-1	13	830	≥ 80	900	-	130	FSQ-13/30/1B-I-G24d=1	69	-
TC-D	G24d-1	13	840	≥ 80	900	-	130	FSQ-13/40/1B-I-G24d=1	69	-
TC-D	G24d-2	18	827	≥ 80	1200	-	140	FSQ-18/27/1B-I-G24d=2	67	-
TC-D	G24d-2	18	830	≥ 80	1200	-	140	FSQ-18/30/1B-I-G24d=2	67	-
TC-D	G24d-2	18	840	≥ 80	1200	-	140	FSQ-18/40/1B-I-G24d=2	67	-
TC-D	G24d-3	26	827	≥ 80	1800	-	160	FSQ-26/27/1B-I-G24d=3	69	-
TC-D	G24d-3	26	830	≥ 80	1800	-	160	FSQ-26/30/1B-I-G24d=3	69	-
TC-D	G24d-3	26	840	≥ 80	1800	-	160	FSQ-26/40/1B-I-G24d=3	69	-
TC-DEL	G24q-1	10	827	≥ 80	-	600	95	FSQ-10/27/1B-E-G24q=1	-	60
TC-DEL	G24q-1	10	830	≥ 80	-	600	95	FSQ-10/30/1B-E-G24q=1	-	60
TC-DEL	G24q-1	10	840	≥ 80	-	600	95	FSQ-10/40/1B-E-G24q=1	-	60
TC-DEL	G24q-1	13	827	≥ 80	-	900	130	FSQ-13/27/1B-E-G24q=1	-	69
TC-DEL	G24q-1	13	830	≥ 80	-	900	130	FSQ-13/30/1B-E-G24q=1	-	69
TC-DEL	G24q-1	13	840	≥ 80	-	900	130	FSQ-13/40/1B-E-G24q=1	-	69

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
TC-DEL	G24q-2	18	827	≥ 80	-	1200	140	FSQ-18/27/1B-E-G24q=2	-	67
TC-DEL	G24q-2	18	830	≥ 80	-	1200	140	FSQ-18/30/1B-E-G24q=2	-	67
TC-DEL	G24q-2	18	840	≥ 80	-	1200	140	FSQ-18/40/1B-E-G24q=2	-	67
TC-DEL	G24q-3	26	827	≥ 80	-	1800	160	FSQ-26/27/1B-E-G24q=3	-	69
TC-DEL	G24q-3	26	830	≥ 80	-	1800	160	FSQ-26/30/1B-E-G24q=3	-	69
TC-DEL	G24q-3	26	840	≥ 80	-	1800	160	FSQ-26/40/1B-E-G24q=3	-	69
TC-T	G24d-1	13	827	≥ 80	900	-	90	FSM-13/27/1B-I-G24d=1	69	-
TC-T	G24d-1	13	830	≥ 80	900	-	90	FSM-13/30/1B-I-G24d=1	69	-
TC-T	G24d-1	13	840	≥ 80	900	-	90	FSM-13/40/1B-I-G24d=1	69	-
TC-T	G24d-2	18	827	≥ 80	1200	-	100	FSM-18/27/1B-I-G24d=2	67	-
TC-T	G24d-2	18	830	≥ 80	1200	-	100	FSM-18/30/1B-I-G24d=2	67	-
TC-T	G24d-2	18	840	≥ 80	1200	-	100	FSM-18/40/1B-I-G24d=2	67	-
TC-T	G24d-3	26	827	≥ 80	1800	-	115	FSM-26/27/1B-I-G24d=3	69	-
TC-T	G24d-3	26	830	≥ 80	1800	-	115	FSM-26/30/1B-I-G24d=3	69	-

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
TC-T	G24d-3	26	840	≥ 80	1800	-	115	FSM-26/40/1B-I-G24d=3	69	-
TC-TEL	G24q-1	13	827	≥ 80	-	900	90	FSMH-13/27/1B-E-G24q-1	-	69
TC-TEL	G24q-1	13	830	≥ 80	-	900	90	FSMH-13/30/1B-E-G24q-1	-	69
TC-TEL	G24q-1	13	840	≥ 80	-	900	90	FSMH-13/40/1B-E-G24q-1	-	69
TC-TEL	G24q-2	18	827	≥ 80	-	1200	100	FSMH-18/27/1B-E-G24q-2	-	67
TC-TEL	G24q-2	18	830	≥ 80	-	1200	100	FSMH-18/30/1B-E-G24q-2	-	67
TC-TEL	G24q-2	18	840	≥ 80	-	1200	100	FSMH-18/40/1B-E-G24q-2	-	67
TC-TEL	G24q-3	26	827	≥ 80	-	1800	115	FSMH-26/27/1B-E-G24q-3	-	69
TC-TEL	G24q-3	26	830	≥ 80	-	1800	115	FSMH-26/30/1B-E-G24q-3	-	69
TC-TEL	G24q-3	26	840	≥ 80	-	1800	115	FSMH-26/40/1B-E-G24q-3	-	69
TC-TEL	G24q-3	32	827	≥ 80	-	2400	130	FSMH-32/27/1B-E-G24q-3	-	75
TC-TEL	G24q-3	32	830	≥ 80	-	2400	130	FSMH-32/30/1B-E-G24q-3	-	75
TC-TEL	G24q-3	32	840	≥ 80	-	2400	130	FSMH-32/40/1B-E-G24q-3	-	75
TC-TEL	G24q-4	42	827	≥ 80	-	3200	155	FSMH-42/27/1B-E-G24q-4	-	76
TC-TEL	G24q-4	42	830	≥ 80	-	3200	155	FSMH-42/30/1B-E-G24q-4	-	76
TC-TEL	G24q-4	42	840	≥ 80	-	3200	155	FSMH-42/40/1B-E-G24q-4	-	76

Lamp type	Base	Wattage (W)	Light colour	Colour rendering index Ra	Lamp rated luminous flux at LLCG (lm)	Lamp rated luminous flux at ECG (lm)	Lamp length / ring diameter (mm)	ILCOS code	Lamp luminous efficiency at LLCG (lm/W)	Lamp luminous efficiency at ECG (lm/W)
TC-F	2G8	24	827	≥ 80	1700	1700	165	FSS-24/27/1B-E-2G8	71	71
TC-F	2G8	24	830	≥ 80	1700	1700	165	FSS-24/30/1B-E-2G8	71	71
TC-F	2G8	24	840	≥ 80	1700	1700	165	FSS-24/40/1B-E-2G8	71	71
TC-F	2G8	36	827	≥ 80	2800	2800	217	FSS-36/27/1B-E-2G8	78	78
TC-F	2G8	36	830	≥ 80	2800	2800	217	FSS-36/30/1B-E-2G8	78	78
TC-F	2G8	36	840	≥ 80	2800	2800	217	FSS-36/40/1B-E-2G8	78	78