

SYSTEM

FINEA

SYSTEM MATRIX



LIGHT CHANNEL SYSTEM

System form	Profile width	Profile colour	Distribution characteristics / optics			Light colour	CRI	System luminous flux		Installation methods		Step lengths 70 mm	Integrated track	Continuous line	LiveLink [®]	CAS+MBI	3h	UR	Through-wiring	Switching type	Suspension lengths	Infeed								
      	  	  	    	 ConVision [®] OFFICE	2700K	 CRI80	 min. 930 lm/m  max. 5,000 lm/m		Recessed, with trim	✓	✓	✓	✓	✓	✓	✓	Quick contact plug	ET	 2 m	Terminal block										
				 ConVision [®] Accenting					Ceiling surface-mounted	✓	✓	✓	✓	✓	✓															
				 Prismatic (CDP)	3000K			 Adapter	Global	✓																				
				 Opal diffuser	4000K				Stucchi		✓																			
				 Drop diffuser	TUNABLE WHITE				Suspended, direct distribution		✓	✓	✓	✓	✓	✓				5 pole	ETDD	 3 m	1,000 mm connection cable with Wieland 1GST3							
				 Black diffuser					Suspended, direct/indirect		✓	✓	✓	✓	✓	✓				5+2 pole	ETDD2	 5 m	1,000 mm connection cable with Wieland 1GST5							
				 Wallwasher					Wall surface-mounted, direct distribution		✓																			
				 Blind segments					Wall surface-mounted, direct/indirect		✓																			