

ENVIRONMENTAL

PRODUCT DECLARATION

PRODUCT ENVIRONMENTAL PROFILE - Combial G2 Floodlight

Reference product: Combial 40 G2 AM9L/80-150/3/ML-MC G1 ET

Registration number	TRLX-00035-V01.01-EN	**Drafting rules**	PCR-ed4-EN-2021 09 06
		Supplemented by	PSR-0014-ed2.0-EN-2023 07 13
Verifier accreditation number	VH31	**Information and reference documents**	www.pep-ecopassport.org
Date of publication	10-2026	**Validity period**	5 years
Independent verification of the declaration and data in compliance with ISO 14025: 2006			
Internal		**External**	x
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain).			
PEPs are compliant with XP C08-100-1:2016 and EN 50693:2019 or NF E38-500:2022			
The components of the present PEP cannot be compared with elements from another program.			
Document complies with ISO 14025:2006 “Environmental labels and declarations. Type III environmental declarations”			

Company information:
Further technical information can be obtained by contacting:
TRILUX GmbH & Co. KG, Heidestraße 4, D-59759 Arnsberg, Germany
or on the website www.trilux.com
or by email support@trilux.com

1. GENERAL INFORMATION

1.1 Product information

LED floodlight for planar lighting and accent lighting. A motion sensor/brightness sensor can be combined with the spotlight as an optional accessory without tools. Pivotable fixing bracket for suspended and vertical mounting. Optical system consists of a PC lens optic. With asymmetric medium wide light distribution. Luminaire luminous flux and light color adjustable in 6 levels (Multilumen, Multicolour). Luminaire luminous flux 7400 lm - 15000 lm, connected load 56 W - 120 W, maximum luminous efficiency of luminaire 143 lm/W. Light colour warm white or neutral white, correlated colour temperature (CCT) 3000 K or 4000 K, general colour rendering index (CRI) Ra > 80. Colour locus tolerance (initial MacAdam) ⩽ 5 SDCM. Mean rated service life L80 (tq 25 °C) = 55,000 h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Flicker: Pst LM ⩽ 1.0 at full load. Spotlight body of die-cast aluminium. Surface coated black (similar to RAL 9005). Dimensions (L x W): 399 mm x 361 mm, luminaire height 59 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP65, impact resistance level in accordance with IEC 62262: IK08. Permissible ambient temperature (ta): 50 °C Windage area Fw = 0,300 m2. Weight: 4,37kg. With electronic control gear unit, switchable. Surge voltage resistance Differential Mode / Common Mode: 6 kV / 8 kV. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

The Combial G2 Floodlight product family comprises a range of product variants with different characteristics, as listed in table 1. These products have the characteristics described in PSR-0014-ed2.0-EN-2023-07-13 and belong to a homogeneous environmental family. The reference product is the Combial 40 G2 AM9L/80-150/3/ML-MC G1 ET and the most important information is summarized in table 2.

Table 1: Products Included in the Combial G2 Floodlight Family

Product variant	TK	TOC	EAN
Combial 40 G2 AM9/80-150/3/ML-MC G1 ETDD	10485010	6001364551	4069072166904
Combial 40 G2 RB8/80-150/3/ML-MC G1 ETDD	10485011	6001364651	4069072166911
Combial 45 G2 AM9/150-250/3/ML-MC G1 ETDD	10485012	6001364751	4069072166928
Combial 45 G2 RB8/150-250/3/ML-MC G1 ETDD	10485013	6001364851	4069072166935
Combial 50 G2 AM9/350-500/3/ML-MC G1 ETDD	10485014	6001364951	4069072166942
Combial 50 G2 RB8/350-500/3/ML-MC G1 ETDD	10485015	6001365051	4069072166959
Combial 30 G2 AM9L/20-50/3/ML-MC G1 ET	10341634	8590040	4018242969173
Combial 40 G2 AM9L/80-150/3/ML-MC G1 ET	10341635	8590140	4018242969180
Combial 45 G2 AM9L/150-250/3/ML-MC G1 ET	10341636	8590240	4018242969197
Combial 50 G2 AM9L/350-500/3/ML-MC G1 ET	10341637	8590340	4018242969203
Combial 30 G2 RB8L/20-50/3/ML-MC G1 ET	10341638	8590440	4018242969210
Combial 40 G2 RB8L/80-150/3/ML-MC G1 ET	10341639	8590540	4018242969227
Combial 45 G2 RB8L/150-250/3/ML-MC G1 ET	10341640	8590640	4018242969234
Combial 50 G2 RB8L/350-500/3/ML-MC G1 ET	10341641	8590740	4018242969241

1. GENERAL INFORMATION

Table 2: Key technological data

Information	Unit	
Light source	-	Internal LED module
Control gear	-	Internal
Color temperature	K	3000/4000
Protection index for water and dust (IP)	-	IP65
Impact resistance index (IK)	-	IK08
Nominal operating voltage	V	220-240
Declared lifetime of the luminaire	Hours	55000
Declaration lifetime of the light source	Hours	55000
Outgoing luminous flux/Useful output flux	Lumen	15000/10000/8000
Electrical input power	W	120/73/56
Luminous efficiency	Lumen/W	125/137/143
Reference use scenario	-	Zone, open space
Lifetime in years according to reference use scenario	yr	13.8

1.2 Goal and Scope

Following information has been used to generate the PEP:

Table 3: Goal and Scope

Information	
Functional unit	Provide lighting that delivers an outgoing artificial luminous flux of 1,000 lumens during a reference lifetime of 35,000 hours
Reference flow / declared unit*	0.042 pieces of product
Life cycle stages covered	Cradle-to-grave and Module D
Product category according to PSR	Luminaires
Product family name	**Combial G2 Floodlight**
Product name	Combial 40 G2 AM9L/80-150/3/ML-MC G1 ET

*The reference flow is calculated as: (1,000/outgoing luminous flux of the analyzed product in lumens) x (35,000/declared product lifetime of the analyzed product in hours). Consequently, the reference flow of the Combial G2 Floodlight corresponds to: (1,000/15,000) x (35,000/55,000) = 0.042

2. CONSTITUENT MATERIALS

2.1 Overview

The product composition is shown in the following table.

Table 4: Product composition

	Weight [in kg]	Share [in %]
Total Weight	5.305	100.00
Product	4.304	81.12
Packaging	1.001	18.88

2.2 Product

The material composition of the product is shown in the following table.

Table 5: Material composition - product

		Weight [in kg]	Share [in %]
Total weight		4.304	100.00
Metals		2.464	57.25
	Aluminium	1.316	30.57
	Steel	1.083	25.17
	Stainless Steel	0.049	1.14
	Copper	0.016	0.36
	Other non-ferrous metals	0.000	0.00
Plastics		0.592	13.76
	Acrylonitrile butadiene styrene (ABS)	0.003	0.06
	Poly Vinyl Chloride (PVC)	0.000	0.00
	Polyamide (PA)	0.009	0.22
	Ethylene Propylene Diene Monomer (EPDM)	0.000	0.00
	Polycarbonate/Polybutylene terephthalate (PC/PBT) blend	0.000	0.00
	Polycarbonate (PC)	0.054	1.26
	Polycarbonate/Acrylonitrile butadiene styrene (PC/ABS) blend	0.000	0.00
	Polymethyl Methacrylate (PMMA)	0.089	2.07
	Polyurethane (PU)	0.000	0.00
	Silicone	0.420	9.76
	Polyethylene (PE)	0.000	0.00
	Polyethylene terephthalate (PET)	0.017	0.40
	Polypropylene (PP)	0.000	0.00
	Polystyrene (PS)	0.000	0.00
	Other plastics or plastics containing additives / fillers	0.000	0.00
Other		1.248	28.99
	Electronics	0.339	7.87
	Batteries	0.000	0.00
	Glass	0.909	21.12
	Paint	0.000	0.00
	Graphite	0.000	0.00

2. CONSTITUENT MATERIALS

2.3 Packaging

The material composition of the packaging is shown in the following table.

Table 6: Material composition - packaging

	Weight [in kg]	Share [in %]
Total weight	1.001	100.00
Paper/Cardboard	0.603	60.24
Plastic	0.000	0.00
Wood	0.398	39.76

3. INFORMATION ON LIFE CYCLE STAGES



3.1 Manufacturing stage (A1-A3)

The manufacturer sources all parts from suppliers. Within the manufacturing site in China, the manufacturer produced Printed Circuit Board Assembly through surface mounting and hole-through mounting process from the Printed Circuit Board using energy and auxiliaries. Then the product was assembled and tested using energy. Afterwards the product is packed in packaging materials and distributed to the client.



3.2 Distribution stage (A4)

The main market for the product is Europe and there is no specific data available. For this reason, an International transport from China to the arrival of the product at the place of use following PEP-PCR-ed4-EN-2021 09 06 is considered in the model: Ship: 19,000 km and Lorry: 1,000 km



3.3 Installation stage (A5)

The product can easily be installed without any special tool. No energy or material input is required. The End-of-life scenario of packaging materials was used according to PSR-0014-ed2.0-EN-2023 07 13. The transport of packaging materials was modelled in accordance with PSR-0014-ed2.0-EN-2023 07 13, assuming a transport distance of 100 km by lorry.



3.4 Use stage (B1-B7)

The product has no direct emissions and no maintenance is required. Since the assigned lifetime of the integrated LED module is 55,000 hours, which is the same as that of Combial G2 Floodlight, no replacement of the light source is required during reference service life. Furthermore, no standard repairs or refurbishments are foreseen. The use of the product does consume electricity, but no water.

The main market for the product is Europe, and the distribution ratio of country/region is listed in the table below:

Table 7: The LCI dataset used in the use stage

Country/Region	Share (%)	Energy model
Germany	31	market for electricity, low voltage | electricity, low voltage | Cutoff, S - DE
France	29	market for electricity, low voltage | electricity, low voltage | Cutoff, S - FR
Poland	10	market for electricity, low voltage | electricity, low voltage | Cutoff, S - PL
Spain	6	market for electricity, low voltage | electricity, low voltage | Cutoff, S - ES
Netherlands	1	market for electricity, low voltage | electricity, low voltage | Cutoff, S - NL
Austria	4	market for electricity, low voltage | electricity, low voltage | Cutoff, S - AT
Rest countries in EU	5	market group for electricity, low voltage | electricity, low voltage | Cutoff, S - RER
Belgium	5	market for electricity, low voltage | electricity, low voltage | Cutoff, S - BE
Switzerland	2	market for electricity, low voltage | electricity, low voltage | Cutoff, S - CH
Arab Emirates	5	market for electricity, low voltage | electricity, low voltage | Cutoff, S - AE
United Kingdom	1	market for electricity, low voltage | electricity, low voltage | Cutoff, S - GB
Italy	1	market for electricity, low voltage | electricity, low voltage | Cutoff, S - IT

3. INFORMATION ON LIFE CYCLE STAGES

3.5 End-of-life stage (C1-C4)

There is no specific data available to calculate the shipment of the product from the installation site to the approved treatment centers. The default distance is 1000 km by lorry was used according to PEP-PCR-ed4-EN-2021 09 06. The product can easily be deinstalled without any special tool. No energy or material input is required. There is no energy LCI dataset used in this stage.

The product and its PCB fall under the Waste from Electrical and Electronic Equipment (WEEE) directive 2012/19/EU. The valuable fractions (Aluminium, Steel and Plastics, etc.) are recycling within the default recycling recovering rate established in EN 50693. The remaining parts, based on mass balance, are sent to sanitary landfill.

3.6 Benefits and loads beyond the system boundaries stage (D)

The reuse/recycling of the product (incl. packaging) and incineration with energy recovery generates environmental benefits by avoiding the production of primary materials or energy. The scope of the Module D is With Net Benefits and the net benefits and loads beyond the system boundaries are calculated using the formulas described in PEP-PCR-ed4-EN-2021 09 06. The amount and type of material flows used for the calculation of benefits are listed in Table 8.

Table 8: Material flows for reuse, recycling and/or recovery per unit of product (declared unit, 15,000 lumens during 55,000 hours)

Information	Unit	Value
Total weight of product going into reuse	kg	0.000
Total weight of product going into recycling	kg	2.382
Share of metals	%	77.08
Share of plastics	%	0.02
Share of others	%	22.90
Total weight of product going into incineration with energy recovery	kg	0.296
Share of metals	%	0.00
Share of plastics	%	100.00
Share of others	%	0.00
Total weight of packaging going into reuse	kg	0.398
Total weight of packaging going into recycling	kg	0.495
Share of Paper/board	%	100.00
Share of Plastics	%	0.00
Total weight of packaging going into incineration with energy recovery	kg	0.054
Share of Paper/board	%	100.00
Share of Plastics	%	0.00

4. ENVIRONMENTAL INFORMATION

The Combial G2 Floodlight evaluated in this PEP are in lined with EN 60598-1.

The primary data collected were representative of a current scenario in terms of geographical coverage and technological, of which coverage averaged 6 months. The environmental information included in this study covers all stages of the life cycle (cradle to grave and Module D: A1-A5, B1-B7, C1-C4 and D). The life cycle is divided into the manufacturing stage (A1-A3), distribution stage (A4), installation stage (A5), use stage (B1-B7, where only module B6 has a non-zero contribution; modules B1, B2, B3, B4, B5 and B7 are equal to 0 and are therefore not reflected in Tables 9 to 12), end-of-life stage (C1-C4), and benefits and loads beyond the system boundaries (Module D). The results refer to the core environmental impact indicators and mandatory indicators describing resource use, waste categories, and output flows according to PEP-PCR-ed4-EN-2021 09 06.

The environmental impacts assessment of the reference product has been performed using openLCA 2.5.0 software. Background datasets have been retrieved from Ecoinvent 3.12 database. The results refer to the core environmental impact indicators and mandatory indicators describing resource use, waste categories, and output flows according to PEP-PCR-ed4-EN-2021 09 06.

4.1 Results per functional unit

The following results of the environmental declaration have been developed, considering an outgoing artificial luminous flux of 1,000 lumens over a reference lifetime of 35,000 hours.

Acronyms: GWP-total=Global Warming Potential total; GWP-biogenic=Global Warming Potential biogenic; GWP-fossil=Global Warming Potential fossil; GWP-luluc=Global Warming Potential land use and land use change; ODP=Ozone Depletion; AP=Acidification; EP=Eutrophication; POCP=Photochemical ozone formation; ADPE=Depletion of abiotic resources-minerals and metals; ADPF=Depletion of abiotic resources-fossil fuels; WDP=Water resource depletion; PERE=Renewable primary energy (without raw material); PERM=Renewable primary energy (raw material); PERT=Total use of renewable primary energy; PENRE=Non-renewable primary energy (without raw material); PENRM=Non-renewable primary energy (raw material); PENRT=Total use of non-renewable primary energy; SM=Use of secondary materials; RSF=Use of renewable secondary fuels; NRSF=Use of non-renewable secondary fuels; FW=Net use of fresh water; HWD=Hazardous waste disposed; NHWD=Non-hazardous waste disposed; RWD=Radioactive waste disposed; CRU=Components for reuse; MFR=Materials for recycling; MER=Materials for energy recovery; EEE=Exported electricity; EET=Exported thermal energy; Biog. C in product=Biogenic carbon content of the product; Biog. C in packaging=Biogenic carbon content of the associated packaging

4. ENVIRONMENTAL INFORMATION

Table 9: Results core environmental impact indicators per functional unit

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
GWP - total	kg CO_2 eq.	1.04E+02	1.48E+00	9.28E-03	3.48E-02	6.54E-02	8.44E-02
GWP - fossil	kg CO_2 eq.	1.04E+02	1.54E+00	9.27E-03	3.13E-02	6.53E-02	2.58E-03
GWP - biogenic	kg CO_2 eq.	2.69E-01	-6.24E-02	2.28E-06	3.54E-03	1.48E-05	8.18E-02
GWP - luluc	kg CO_2 eq.	1.50E-01	2.87E-03	4.08E-06	1.39E-05	3.73E-05	3.18E-06
ODP	kg CFC-11 eq.	2.90E-06	1.33E-06	1.27E-10	1.02E-10	9.80E-10	3.89E-11
AP	Mole of H+ eq.	4.76E-01	1.36E-02	3.16E-05	1.87E-04	8.04E-04	1.34E-05
EP - freshwater	kg P eq.	1.07E-01	1.08E-03	1.01E-06	6.54E-06	4.41E-06	3.13E-07
EP - marine	kg N eq.	8.78E-02	1.83E-03	1.03E-05	3.86E-05	3.21E-04	5.84E-06
EP- terrestrial	Mole of N eq.	7.46E-01	2.01E-02	1.11E-04	4.11E-04	3.56E-03	5.33E-05
POCP	kg NMVOC eq.	2.34E-01	6.52E-03	4.37E-05	1.09E-04	9.92E-04	2.02E-05
ADPE	kg Sb eq.	1.45E-03	1.37E-04	3.07E-08	1.50E-07	1.37E-07	9.52E-09
ADPF	MJ	2.26E+03	1.83E+01	1.28E-01	3.31E-01	8.60E-01	3.25E-02
WDP	m^3 world equiv.	4.15E+01	6.02E-01	7.34E-04	4.33E-03	3.87E-03	-3.33E-05

Impact category	Unit	Use	End of life				Benefits*
		B6	C1	C2	C3	C4	D
GWP - total	kg CO_2 eq.	1.02E+02	0.00E+00	1.86E-02	5.18E-02	1.51E-03	-3.85E-01
GWP - fossil	kg CO_2 eq.	1.02E+02	0.00E+00	1.86E-02	5.17E-02	1.51E-03	-3.83E-01
GWP - biogenic	kg CO_2 eq.	2.46E-01	0.00E+00	4.36E-06	9.41E-05	5.10E-07	-1.10E-03
GWP - luluc	kg CO_2 eq.	1.47E-01	0.00E+00	6.76E-06	1.21E-05	2.83E-07	-8.01E-04
ODP	kg CFC-11 eq.	1.57E-06	0.00E+00	4.39E-10	1.60E-10	1.41E-11	-3.51E-09
AP	Mole of H+ eq.	4.61E-01	0.00E+00	4.38E-05	6.86E-05	3.42E-06	-2.46E-03
EP - freshwater	kg P eq.	1.06E-01	0.00E+00	1.37E-06	4.06E-06	4.58E-08	-1.66E-04
EP - marine	kg N eq.	8.55E-02	0.00E+00	1.21E-05	1.80E-05	2.63E-05	-4.36E-04
EP- terrestrial	Mole of N eq.	7.22E-01	0.00E+00	1.31E-04	1.82E-04	1.46E-05	-4.56E-03
POCP	kg NMVOC eq.	2.26E-01	0.00E+00	7.75E-05	5.39E-05	5.48E-06	-1.36E-03
ADPE	kg Sb eq.	1.31E-03	0.00E+00	5.47E-08	3.26E-07	7.86E-10	-6.47E-06
ADPF	MJ	2.24E+03	0.00E+00	2.81E-01	1.13E-01	1.17E-02	-4.18E+00
WDP	m^3 world equiv.	4.08E+01	0.00E+00	1.65E-03	2.96E-03	-1.61E-03	-1.37E-01

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

Table 10: Results indicators describing resource use, waste categories, and output flows per functional unit

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
PERE	MJ	4.99E+02	2.15E+00	1.79E-03	4.42E-02	9.37E-03	8.22E-04
PERM	MJ	7.09E-01	7.09E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	4.99E+02	2.86E+00	1.79E-03	4.42E-02	9.37E-03	8.22E-04
PENRE	MJ	2.26E+03	1.79E+01	1.28E-01	3.31E-01	8.60E-01	3.25E-02
PENRM	MJ	4.05E-01	4.05E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	2.26E+03	1.83E+01	1.28E-01	3.31E-01	8.60E-01	3.25E-02
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m^3	9.62E-01	1.39E-02	1.66E-05	1.00E-04	8.42E-05	-9.60E-07
HWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NHWD	kg	7.13E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.30E-03
RWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CRU	kg	1.69E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.69E-02
MFR	kg	1.25E-01	0.00E+00	0.00E+00	2.63E-03	0.00E+00	2.10E-02
MER	kg	1.49E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.30E-03
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in product	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in packaging	kg of C	2.12E-02	2.12E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Impact category	Unit	Use	End of life				Benefits*
		B6	C1	C2	C3	C4	D
PERE	MJ	4.96E+02	0.00E+00	4.36E-03	1.33E-02	1.22E-04	-1.04E+00
PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	4.96E+02	0.00E+00	4.36E-03	1.33E-02	1.22E-04	-1.04E+00
PENRE	MJ	2.24E+03	0.00E+00	2.81E-01	1.13E-01	1.17E-02	-4.19E+00
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	2.24E+03	0.00E+00	2.81E-01	1.13E-01	1.17E-02	-4.19E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m^3	9.48E-01	0.00E+00	3.71E-05	6.81E-05	-3.76E-05	-3.18E-03
HWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NHWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	6.90E-02	0.00E+00
RWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.01E-01	0.00E+00
MER	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.25E-02	0.00E+00
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in product	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in packaging	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

4.2 Results per unit of product

The following results of the environmental declaration have been developed by considering one product (outgoing artificial luminous flux of 15,000 lumens over a reference lifetime of 55,000 hours).

Table 11: Results core environmental impact indicators per unit of product

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
GWP - total	kg CO_2 eq.	2.45E+03	3.49E+01	2.19E-01	8.21E-01	1.54E+00	1.99E+00
GWP - fossil	kg CO_2 eq.	2.44E+03	3.63E+01	2.18E-01	7.37E-01	1.54E+00	6.09E-02
GWP - biogenic	kg CO_2 eq.	6.35E+00	-1.47E+00	5.38E-05	8.35E-02	3.50E-04	1.93E+00
GWP - luluc	kg CO_2 eq.	3.54E+00	6.77E-02	9.61E-05	3.28E-04	8.78E-04	7.51E-05
ODP	kg CFC-11 eq.	6.83E-05	3.13E-05	3.00E-09	2.41E-09	2.31E-08	9.16E-10
AP	Mole of H+ eq.	1.12E+01	3.20E-01	7.45E-04	4.42E-03	1.90E-02	3.15E-04
EP - freshwater	kg P eq.	2.53E+00	2.54E-02	2.39E-05	1.54E-04	1.04E-04	7.39E-06
EP - marine	kg N eq.	2.07E+00	4.32E-02	2.42E-04	9.09E-04	7.57E-03	1.38E-04
EP- terrestrial	Mole of N eq.	1.76E+01	4.74E-01	2.62E-03	9.68E-03	8.39E-02	1.26E-03
POCP	kg NMVOC eq.	5.52E+00	1.54E-01	1.03E-03	2.57E-03	2.34E-02	4.77E-04
ADPE	kg Sb eq.	3.42E-02	3.23E-03	7.23E-07	3.54E-06	3.22E-06	2.24E-07
ADPF	MJ	5.32E+04	4.31E+02	3.01E+00	7.81E+00	2.03E+01	7.66E-01
WDP	m^3 world equiv.	9.77E+02	1.42E+01	1.73E-02	1.02E-01	9.13E-02	-7.85E-04

Impact category	Unit	Use	End of life				Benefits*
		B6	C1	C2	C3	C4	D
GWP - total	kg CO_2 eq.	2.41E+03	0.00E+00	4.39E-01	1.22E+00	3.56E-02	-9.07E+00
GWP - fossil	kg CO_2 eq.	2.40E+03	0.00E+00	4.39E-01	1.22E+00	3.56E-02	-9.02E+00
GWP - biogenic	kg CO_2 eq.	5.81E+00	0.00E+00	1.03E-04	2.22E-03	1.20E-05	-2.60E-02
GWP - luluc	kg CO_2 eq.	3.47E+00	0.00E+00	1.59E-04	2.84E-04	6.66E-06	-1.89E-02
ODP	kg CFC-11 eq.	3.69E-05	0.00E+00	1.04E-08	3.77E-09	3.31E-10	-8.28E-08
AP	Mole of H+ eq.	1.09E+01	0.00E+00	1.03E-03	1.62E-03	8.06E-05	-5.81E-02
EP - freshwater	kg P eq.	2.50E+00	0.00E+00	3.24E-05	9.58E-05	1.08E-06	-3.91E-03
EP - marine	kg N eq.	2.02E+00	0.00E+00	2.86E-04	4.24E-04	6.20E-04	-1.03E-02
EP- terrestrial	Mole of N eq.	1.70E+01	0.00E+00	3.09E-03	4.29E-03	3.44E-04	-1.08E-01
POCP	kg NMVOC eq.	5.34E+00	0.00E+00	1.83E-03	1.27E-03	1.29E-04	-3.20E-02
ADPE	kg Sb eq.	3.10E-02	0.00E+00	1.29E-06	7.68E-06	1.85E-08	-1.53E-04
ADPF	MJ	5.27E+04	0.00E+00	6.62E+00	2.67E+00	2.75E-01	-9.86E+01
WDP	m^3 world equiv.	9.63E+02	0.00E+00	3.88E-02	6.98E-02	-3.80E-02	-3.23E+00

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

Table 12: Results indicators describing resource use, waste categories, and output flows per unit of product

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
PERE	MJ	1.18E+04	5.07E+01	4.21E-02	1.04E+00	2.21E-01	1.94E-02
PERM	MJ	1.67E+01	1.67E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	1.18E+04	6.74E+01	4.21E-02	1.04E+00	2.21E-01	1.94E-02
PENRE	MJ	5.32E+04	4.22E+02	3.01E+00	7.81E+00	2.03E+01	7.66E-01
PENRM	MJ	9.55E+00	9.55E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	5.32E+04	4.31E+02	3.01E+00	7.81E+00	2.03E+01	7.66E-01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m^3	2.27E+01	3.27E-01	3.91E-04	2.37E-03	1.98E-03	-2.26E-05
HWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NHWD	kg	1.68E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.43E-02
RWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CRU	kg	3.98E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.98E-01
MFR	kg	2.94E+00	0.00E+00	0.00E+00	6.19E-02	0.00E+00	4.95E-01
MER	kg	3.50E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.43E-02
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in product	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in packaging	kg of C	5.01E-01	5.01E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Impact category	Unit	Use	End of life				Benefits*
		B6	C1	C2	C3	C4	D
PERE	MJ	1.17E+04	0.00E+00	1.03E-01	3.15E-01	2.88E-03	-2.45E+01
PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	1.17E+04	0.00E+00	1.03E-01	3.15E-01	2.88E-03	-2.45E+01
PENRE	MJ	5.27E+04	0.00E+00	6.62E+00	2.67E+00	2.75E-01	-9.87E+01
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT	MJ	5.27E+04	0.00E+00	6.62E+00	2.67E+00	2.75E-01	-9.87E+01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m^3	2.23E+01	0.00E+00	8.75E-04	1.60E-03	-8.85E-04	-7.49E-02
HWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NHWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.63E+00	0.00E+00
RWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.38E+00	0.00E+00
MER	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.96E-01	0.00E+00
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in product	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biog. C in packaging	kg of C	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

*Benefits and loads beyond the system boundaries

5. EXTRAPOLATION RULE FOR PRODUCT VARIANTS

5.1 Extrapolation coefficients

The extrapolation coefficients included in the PEP have been developed according to the valid PCR & PSR. The extrapolation coefficients at product level (declared unit) are listed in table 13.

Table 13: The extrapolation coefficients at the product level (declared unit)

Product variant	Fabrication stage	Distribution stage	Installation stage	Use stage	End of life stage	Module D
Combial 40 G2 AM9L/80-150/3/ML-MC G1 ET	1.00	1.00	1.00	1.00	1.00	1.00
Combial 30 G2 AM9L/20-50/3/ML-MC G1 ET	0.40	0.37	0.51	0.33	0.34	0.41
Combial 45 G2 AM9L/150-250/3/ML-MC G1 ET	1.35	1.34	1.40	1.38	1.33	1.35
Combial 30 G2 RB8L/20-50/3/ML-MC G1 ET	0.39	0.36	0.51	0.33	0.33	0.40
Combial 40 G2 RB8L/80-150/3/ML-MC G1 ET	0.98	0.98	1.00	1.00	0.98	0.98
Combial 45 G2 RB8L/150-250/3/ML-MC G1 ET	1.32	1.31	1.40	1.38	1.29	1.32
Combial 50 G2 AM9L/350-500/3/ML-MC G1 ET	2.85	2.70	3.83	2.85	2.44	2.93
Combial 50 G2 RB8L/350-500/3/ML-MC G1 ET	2.79	2.64	3.83	2.85	2.37	2.89
Combial 50 G2 AM9L/350-500/3/ML-MC G1 ETDD	2.85	2.72	3.83	1.43	2.47	2.93
Combial 50 G2 RB8L/350-500/3/ML-MC G1 ETDD	2.79	2.67	3.83	1.43	2.40	2.88
Combial 40 G2 AM9L/80-150/3/ML-MC G1 ETDD	0.97	0.96	1.00	0.50	0.95	0.97
Combial 45 G2 AM9L/150-250/3/ML-MC G1 ETDD	1.35	1.33	1.40	0.69	1.31	1.35
Combial 40 G2 RB8L/80-150/3/ML-MC G1 ETDD	0.96	0.94	1.00	0.50	0.93	0.96
Combial 45 G2 RB8L/150-250/3/ML-MC G1 ETDD	1.32	1.30	1.40	0.69	1.28	1.32

Note: The extrapolation at the level of the functional unit needs to take into account according to the following formula:

$$\textbf{Extrapolation coefficients at the product} \times \left(\frac{\textbf{lighting output of reference product (lumens)}}{\textbf{lighting output of concerned product (lumens)}}\right)$$

Legal Disclaimer

The information contained in this document is provided for general information purposes only and represents a standard-based environmental declaration derived from the assumptions, data and methodologies defined by the applicable standards, product category rules (PCR) and specific product rules (PSR) described herein. It does not constitute a guarantee or warranty of specific product properties, nor does it form part of any contractual agreement. The characteristics of products are binding only if expressly agreed in the relevant contract.

While TRILUX has taken reasonable care to ensure the accuracy of the data, no representation or warranty is given, either express or implied, regarding the completeness, accuracy or fitness for a particular purpose of the information provided.

The values and results stated in this EPD are valid only within the defined scope, system boundaries and assumptions. They are not intended to be used as the sole basis for environmental assessments of installations or buildings and may not be directly comparable with data from EPDs based on different standards or product category rules. TRILUX shall not be liable for any damages or consequences arising from the use or interpretation of the information contained in this document, except in cases of mandatory liability under applicable law.

Subject to technical modifications and errors.

All product names and trademarks mentioned are the property of their respective owners.