

PRODUCT ENVIRONMENTAL PROFILE - JUNO PL

Reference product: JNPL H20 L-OVL 30-830 C37 ET L1,5 01

Registration number	TRLX-00036-V01.01-EN	**Drafting rules**	PCR-ed-EN-2021 09 06
		Supplemented by	PSR-0014-ed2.0-EN2023 07 13
Verifier accreditation number	VH45	**Information and reference documents**	www.pep-ecopassport.org
Date of issue	05-2026	**Validity period**	5 years
Independent verification of the declaration and data, in compliance with ISO 14025: 2006.			
Internal		**External**	X
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain).			
PEPs are compliant with XP C08-100-1:2016 or EN 50693:2019.			
The components of the present PEP may not be compared with components from any other program.			
Document complies with ISO 14025:2006 „Environmental labels and declarations. Type III environmental declarations“.			

Company information:
Further technical information can be obtained by contacting:
TRILUX GmbH & Co. KG, Heidestraße 4, D-59759 Arnsberg, Germany
or on the website www.trilux.com
or by email support@trilux.com

1. GENERAL INFORMATION

1.1 Product information

JUNO suspended luminaire, 3000 K / 3000 lm / CRI > 80 / 19 W, system luminous flux: 2910 lm / 153 lm/W, Lifespan: L80 / B10 (25 °C) = 50.000 h, Luminaire colour: RAL 9016 traffic white Mounting: Surface mounted H20, RAL 9016, Suspension length: 1500mm, lens Oval light Distribution, Cover: without, Optic colour: RAL 9005 jet black

1. GENERAL INFORMATION

Table 1: Key technological data

Information	Unit	
Light source	-	Integrated LED module
Power supply	-	Integrated power supply
Color temperature	K	3,000
Protection index for water and dust (IP)	-	IP20
Impact resistance index (IK)	-	IK00
Nominal operating voltage	V	220-240
Declared lifetime of the luminaire	hr	50,000
Outgoing luminous flux/Useful output flux	lm	2,910
Electrical input power	W	19
Luminous efficiency	lm/W	153
Dimension	mm	178 x 115 x 74
Reference use scenario	-	Retail
Lifetime in years according to reference use scenario	yr	10

1.2 Goal and Scope

Following information has been used to generate the PEP:

Table 2: Goal and Scope

Information	
Functional unit	Provide lighting that delivers an outgoing artificial luminous flux of 1,000 lumens during a reference lifetime of 35,000 hours
Reference flow / declared unit*	0.2405 pieces of product
Life cycle stages covered	Cradle-to-grave and Module D
Product category according to PSR	Luminaires
Product family name	Juno PL
Product name	JNPL H20 L-OVL 30-830 C37 ET L1,5 01
All products of the product family ("X" refer to placeholders for different product codes)	Please find a full list of aliases on Table 12 within this document.

*The reference flow is calculated as: (1,000/outgoing luminous flux of the analyzed product in lumens) x (35,000/declared product lifetime of the analyzed product in hours). Consequently, the reference flow of the following product correspond to: (1,000/2,910) x (35,000/50,000) = 0.2405

2. CONSTITUENT MATERIALS

2.1 Overview

The product composition is shown in the following table.

Table 3: Product composition

	Weight [in kg]	Share [in %]
Total Weight	2.032	100,0
Product	1.770	87,1
Packaging	0.262	12,9

2.2 Product

The material composition of the product is shown in the following table.

Table 4: Material composition - product

		Weight [in kg]	Share [in %]
Total weight		1.770	100,0
Metals		1.288	72,8
	Aluminium	0.881	49,8
	Steel	0.383	21,6
	Stainless Steel	0.020	1,1
	Copper	0.004	0,2
Plastics		0.401	22,7
	Acrylonitrile butadiene styrene (ABS)	0.000	0,0
	Poly Vinyl Chloride (PVC)	0.026	1,5
	Polyamide (PA)	0.002	0,1
	Ethylene Propylene Diene Monomer (EPDM)	0.000	0,0
	Polycarbonate/Polybutylene terephthalate (PC/PBT) blend	0.003	0,2
	Polycarbonate (PC)	0.053	3,0
	Polycarbonate/Acrylonitrile butadiene styrene (PC/ABS) blend	0.000	0,0
	Polymethyl Methacrylate (PMMA)	0.316	17,9
	Polyurethane (PU)	0.000	0,0
	Silicone	0.000	0,0
	Polyethylene (PE)	0.001	0,1
Graphite		0.000	0,0
Other		0.081	4,6
	Electronics	0.081	4,6
	Batteries	0.000	0,0
	Glass	0.000	0,0
	Paint	0.000	0,0

2.3 Packaging

The product composition is shown in the following table.

Table 5: Material composition - packaging

	Weight [in kg]	Share [in %]
Total weight	0.262	100,0
Paper/Cardboard	0.262	100,0
Plastic	0.000	0,0
Wood	0.000	0,0

3. INFORMATION ON LIFE CYCLE STAGES



3.1 Manufacturing stage (A1-A3)

The manufacturer sources all parts from different suppliers. The production site is in Germany. During the production is no energy or material input is required.Material were modelled with a global process from ecoinvent 3.9.1.Further, transport distances for materials were calculated according to PEP-PCR-ed4- EN-2021 09 06 since no specific data regarding transport were available. Ship: 19,000 km, Lorry: 1,000 km. A basic assumption in accordance with PSR-0014-ed2.0-EN-2023 07 13 was used to model the waste streams of the packaging for the raw materials. According to the PSR 5% of the luminaire's mass shall be considered as packaging (14,9 kg*0,05= 0,745 kg). The packaging materials shall then be split as follows: Wood: 50% (0,3725 kg), Cardboard: 40 % (0,298 kg), LDPE:10 % (0,0745 kg). Further, transportation from the production site to storage site was modeled with 78 km according to the information given by the supplier. Also,to produce the luminaire a marginal sum of electricity was used which was cut-off. Addidtionally, for production of the luminaire only recyclable waste from cardboard was generated with transportation to the location of the end-of-life-stage of 10 km according to manufacturer specific data.



3.2 Distribution stage (A4)

The main market of the product is Europe and there is no specific data available. For this reason, an intracontinental transport (3,500 km by truck (diesel driven, EURO 0-6, >27t payload) to the place of use following PEP-PCR–ed4-EN-2021 09 06 is considered.



3.3 Installation stage (A5)

The product can easily be installed without any special tool. No energy or material input is required. Packaging waste is treated according to the scenario given in PEP-PSR-0014-ed2-EN-2023 07 13 by PEP ecopassport.



3.4 Use stage (B1-B7)

The product has no direct emissions (B1). No maintenance (B2), repair (B3), replacement (B4), or refurbishment (B5) is required. The use of the product does consume electricity (B6), but no water (B7).

The operational electricity consumption over the entire lifetime of the product is 950 kWh. It has been calculated according to PSR edition 2. The used energy model refers to an average European electricity grid mix from Sphera's Managed LCA Content.



3.5 End-of-life stage (C1-C4)

The product falls under the Waste from Electrical and Electronic Equipment (WEEE) directive 2012/19/ EU. Therefore, a collection rate of 100% and a typical end-of-life scenario for electronic products is assumed. All (mechanical and electronic) metals are recycled. Plastic & renewable materials are incinerated with energy recovery. Batteries & glass are landfilled. For the transport to end-of-life treatment 1,000 km by truck according to PEP PCR is considered.

3.6 Benefits and loads beyond the system boundaries stage (D)

The recycling of the product (incl. packaging) and incineration with energy recovery generates environmental benefits and loads beyond the system boundaries (D). The calculation of this module is in line with the formulars described in PEP-PCR–ed4-EN-2021 09 06. The amount of the material flows used for the calculation are listed in the table below.

Table 6: Material flows for benefits and loads beyond the system boundaries per functional unit

	Weight [in kg]
Total weight going into incineration with energy recovery	0.481
Total weight going into recycling	1.288

4. ENVIRONMENTAL INFORMATION

The environmental information included in this study cover all stages of the life cycle („cradle-to grave").
The life cycle is divided into manufacturing stage (A1-A3), distribution stage (A4), installation stage (A5), use stage (B1-B7, but only applicable modules are shown), End-of-life stage (C1-C4) and benefits and loads beyond the system boundaries (D). The results refer to the core environmental impact indicators and mandatory indicators describing resource use, waste categories, and output flows according to PEP-PCR–ed4,- EN-2021 09 06 and EN 15804+A2:2019.

The results have been calculated using the LCA Software "LCA for Experts 10" and the LCI database "Sphera Managed LCA Content".

4.1 Results per functional unit

The following results of the environmental declaration have been developed, considering an outgoing artificial luminous flux of 1,000 lumens over a reference lifetime of 35,000 hours.

Acronyms: GWP-total=Global Warming Potential total; GWP-biogenic=Global Warming Potential biogenic; GWP-fossil=Global Warming Potential fossil; GWP-luluc=Global Warming Potential land use and land use change; ODP=Ozone Depletion; AP=Acidification; EP=Eutrophication; POCP=Photochemical ozone formation; ADPE=Depletion of abiotic resources-minerals and metals; ADPF=Depletion of abiotic resources-fossil fuels; WDP=Water resource depletion; PERE=Renewable primary energy (without raw material); PERM=Renewable primary energy (raw material); PERT=Total use of renewable primary energy; PENRE=Non-renewable primary energy (without raw material); PENRM=Non-renewable primary energy (raw material); PENRT=Total use of non-renewable primary energy; SM=Use of secondary materials; RSF=Use of renewable secondary fuels; NRSF=Use of non-renewable secondary fuels; FW=Net use of fresh water; HWD=Hazardous waste disposed; NHWD=Non-hazardous waste disposed; RWD=Radioactive waste disposed; CRU=Components for reuse; MFR=Materials for recycling; MER=Materials for energy recovery; EEE=Exported electricity; EET=Exported thermal energy; Biog. C in product=Biogenic carbon content of the product; Biog. C in packaging=Biogenic carbon content of the associated packaging

4. ENVIRONMENTAL INFORMATION

Table 7: Results core environmental impact indicators per functional unit

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
GWP - total	kg CO2 eq.	7.78E+01	3.96E+00	3.73E-02	1.90E-01	1.37E-01	5.35E-02
GWP - fossil	kg CO2 eq.	7.68E+01	3.94E+00	3.53E-02	1.73E-01	1.35E-01	3.53E-02
GWP - biogenic	kg CO2 eq.	7.82E-01	-4.07E-04	1.66E-03	1.68E-02	1.95E-03	1.81E-02
GWP - luluc	kg CO2 eq.	2.56E-01	1.54E-02	3.34E-04	7.34E-04	3.76E-04	1.56E-04
ODP	kg CFC-11 eq.	1.67E-09	2.42E-11	5.70E-15	1.35E-12	1.54E-14	8.31E-14
AP	Mole of H+ eq.	1.79E-01	1.76E-02	1.32E-04	4.13E-04	2.22E-03	8.93E-05
EP - freshwater	kg P eq.	1.62E-04	3.51E-06	8.82E-08	3.12E-06	1.23E-07	7.12E-07
EP - marine	kg N eq.	4.25E-02	3.41E-03	5.11E-05	1.93E-04	7.97E-04	4.68E-05
EP- terrestrial	Mole of N eq.	4.74E-01	3.72E-02	5.52E-04	1.80E-03	8.73E-03	4.03E-04
POCP	kg NMVOC eq.	1.07E-01	1.03E-02	1.25E-04	3.74E-04	2.19E-03	7.42E-05
ADPE	kg Sb eq.	1.51E-04	1.36E-04	2.24E-09	6.02E-08	4.89E-09	2.18E-08
ADPF	MJ	1.53E+03	4.98E+01	4.55E-01	2.09E+00	1.62E+00	4.74E-01
WDP	m^3 world equiv.	1.90E+01	8.59E-01	1.54E-04	1.71E-02	3.50E-04	4.22E-03

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	D
GWP - total	kg CO2 eq.	0.00E+00	7.32E+01	3.30E-02	2.60E-01	1.22E-06	-2.12E+00
GWP - fossil	kg CO2 eq.	0.00E+00	7.22E+01	3.11E-02	2.60E-01	1.18E-06	-2.18E+00
GWP - biogenic	kg CO2 eq.	0.00E+00	7.42E-01	1.61E-03	2.55E-05	3.86E-08	6.50E-02
GWP - luluc	kg CO2 eq.	0.00E+00	2.38E-01	3.24E-04	3.35E-05	4.83E-09	-4.99E-03
ODP	kg CFC-11 eq.	0.00E+00	1.64E-09	5.23E-15	1.42E-13	3.28E-18	-3.03E-11
AP	Mole of H+ eq.	0.00E+00	1.58E-01	5.67E-05	5.78E-05	8.32E-09	-8.02E-03
EP - freshwater	kg P eq.	0.00E+00	1.54E-04	8.49E-08	1.86E-08	1.75E-12	-2.36E-06
EP - marine	kg N eq.	0.00E+00	3.79E-02	2.41E-05	1.56E-05	2.18E-09	-1.80E-03
EP- terrestrial	Mole of N eq.	0.00E+00	4.25E-01	2.57E-04	2.67E-04	2.37E-08	-1.96E-02
POCP	kg NMVOC eq.	0.00E+00	9.41E-02	5.09E-05	4.16E-05	6.51E-09	-5.16E-03
ADPE	kg Sb eq.	0.00E+00	1.50E-05	2.10E-09	1.35E-09	7.28E-14	-1.40E-05
ADPF	MJ	0.00E+00	1.47E+03	4.04E-01	1.81E-01	1.54E-05	-2.67E+01
WDP	m^3 world equiv.	0.00E+00	1.81E+01	1.44E-04	2.64E-02	1.27E-07	-2.01E-01

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

Table 8: Results indicators describing resource use, waste categories, and output flows per functional unit

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
PERE	MJ	1.02E+03	1.58E+01	3.15E-02	5.00E-01	4.07E-02	2.23E-01
PERM	MJ	1.21E+00	3.24E-01	0.00E+00	9.78E-01	0.00E+00	-9.41E-02
PERT	MJ	1.02E+03	1.61E+01	3.15E-02	1.48E+00	4.07E-02	1.29E-01
PENRE	MJ	1.53E+03	4.71E+01	4.55E-01	2.12E+00	1.62E+00	4.74E-01
PENRM	MJ	-9.46E-02	2.74E+00	0.00E+00	-3.46E-02	0.00E+00	0.00E+00
PENRT	MJ	1.53E+03	4.98E+01	4.55E-01	2.09E+00	1.62E+00	4.74E-01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m3	8.18E-01	3.46E-02	1.57E-05	9.57E-04	2.44E-05	2.83E-04
HWD	kg	2.10E-06	2.73E-08	1.80E-11	1.92E-08	5.88E-11	7.01E-09
NHWD	kg	2.01E+00	7.77E-01	6.12E-05	5.58E-02	1.58E-04	5.53E-03
RWD	kg	2.34E-01	1.33E-03	8.31E-07	5.94E-05	2.25E-06	1.13E-05
MFR	kg	3.77E-01	0.00E+00	0.00E+00	1.56E-02	0.00E+00	5.18E-02
MER	kg	1.52E-01	0.00E+00	0.00E+00	3.03E-02	0.00E+00	5.68E-03
EEE	MJ	4.21E-01	1.05E-02	0.00E+00	0.00E+00	0.00E+00	1.45E-02
EET	MJ	9.59E-01	1.87E-02	0.00E+00	0.00E+00	0.00E+00	2.21E-02
Biog. C in packaging	kg	3.32E+00	8.21E-01	0.00E+00	2.50E+00	0.00E+00	0.00E+00

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	D
PERE	MJ	0.00E+00	1.01E+03	3.04E-02	7.39E-02	2.98E-06	-1.66E+01
PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	0.00E+00	1.01E+03	3.04E-02	7.39E-02	2.98E-06	-1.66E+01
PENRE	MJ	0.00E+00	1.47E+03	4.04E-01	2.98E+00	1.54E-05	-2.67E+01
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	-2.80E+00	0.00E+00	0.00E+00
PENRT	MJ	0.00E+00	1.47E+03	4.04E-01	1.81E-01	1.54E-05	-2.67E+01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.99E-01
FW	m3	0.00E+00	7.82E-01	1.50E-05	6.42E-04	3.73E-09	-9.83E-03
HWD	kg	0.00E+00	2.05E-06	1.62E-11	3.94E-10	3.38E-15	-2.60E-08
NHWD	kg	0.00E+00	1.14E+00	5.64E-05	2.76E-02	7.70E-05	-5.70E-01
RWD	kg	0.00E+00	2.32E-01	7.62E-07	1.11E-05	1.64E-10	-1.35E-03
MFR	kg	0.00E+00	0.00E+00	0.00E+00	3.10E-01	0.00E+00	0.00E+00
MER	kg	0.00E+00	0.00E+00	0.00E+00	1.16E-01	0.00E+00	0.00E+00
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	3.96E-01	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	9.18E-01	0.00E+00	0.00E+00
Biog. C in packaging	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

4.2 Results per unit of product

The following results of the environmental declaration have been developed, considering one piece of product.

Table 9: Results core environmental impact indicators per unit of product

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
GWP - total	kg CO2 eq.	3.24E+02	1.65E+01	1.55E-01	7.90E-01	5.69E-01	2.23E-01
GWP - fossil	kg CO2 eq.	3.19E+02	1.64E+01	1.47E-01	7.18E-01	5.60E-01	1.47E-01
GWP - biogenic	kg CO2 eq.	3.25E+00	-1.69E-03	6.91E-03	6.98E-02	8.11E-03	7.53E-02
GWP - luluc	kg CO2 eq.	1.06E+00	6.41E-02	1.39E-03	3.05E-03	1.56E-03	6.49E-04
ODP	kg CFC-11 eq.	6.94E-09	1.01E-10	2.37E-14	5.61E-12	6.39E-14	3.45E-13
AP	Mole of H+ eq.	7.43E-01	7.31E-02	5.49E-04	1.72E-03	9.23E-03	3.71E-04
EP - freshwater	kg P eq.	6.74E-04	1.46E-05	3.67E-07	1.30E-05	5.11E-07	2.96E-06
EP - marine	kg N eq.	1.76E-01	1.42E-02	2.12E-04	8.02E-04	3.31E-03	1.95E-04
EP- terrestrial	Mole of N eq.	1.97E+00	1.55E-01	2.30E-03	7.50E-03	3.63E-02	1.68E-03
POCP	kg NMVOC eq.	4.46E-01	4.30E-02	5.21E-04	1.55E-03	9.12E-03	3.08E-04
ADPE	kg Sb eq.	6.27E-04	5.65E-04	9.31E-09	2.50E-07	2.03E-08	9.07E-08
ADPF	MJ	6.35E+03	2.07E+02	1.89E+00	8.67E+00	6.75E+00	1.97E+00
WDP	m^3 world equiv.	7.90E+01	3.57E+00	6.42E-04	7.12E-02	1.46E-03	1.75E-02

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	D
GWP - total	kg CO2 eq.	0.00E+00	3.04E+02	1.37E-01	1.08E+00	5.07E-06	-8.80E+00
GWP - fossil	kg CO2 eq.	0.00E+00	3.00E+02	1.29E-01	1.08E+00	4.89E-06	-9.05E+00
GWP - biogenic	kg CO2 eq.	0.00E+00	3.08E+00	6.70E-03	1.06E-04	1.60E-07	2.70E-01
GWP - luluc	kg CO2 eq.	0.00E+00	9.90E-01	1.35E-03	1.39E-04	2.01E-08	-2.07E-02
ODP	kg CFC-11 eq.	0.00E+00	6.84E-09	2.17E-14	5.90E-13	1.36E-17	-1.26E-10
AP	Mole of H+ eq.	0.00E+00	6.57E-01	2.36E-04	2.40E-04	3.46E-08	-3.33E-02
EP - freshwater	kg P eq.	0.00E+00	6.42E-04	3.53E-07	7.75E-08	7.27E-12	-9.80E-06
EP - marine	kg N eq.	0.00E+00	1.58E-01	1.00E-04	6.48E-05	9.04E-09	-7.49E-03
EP- terrestrial	Mole of N eq.	0.00E+00	1.77E+00	1.07E-03	1.11E-03	9.86E-08	-8.16E-02
POCP	kg NMVOC eq.	0.00E+00	3.91E-01	2.12E-04	1.73E-04	2.71E-08	-2.15E-02
ADPE	kg Sb eq.	0.00E+00	6.24E-05	8.71E-09	5.63E-09	3.03E-13	-5.81E-05
ADPF	MJ	0.00E+00	6.12E+03	1.68E+00	7.51E-01	6.42E-05	-1.11E+02
WDP	m^3 world equiv.	0.00E+00	7.52E+01	5.99E-04	1.10E-01	5.29E-07	-8.37E-01

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

Table 10: Results indicators describing resource use, waste categories, and output flows per unit of product

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
PERE	MJ	4.25E+03	6.56E+01	1.31E-01	2.08E+00	1.69E-01	9.26E-01
PERM	MJ	5.02E+00	1.35E+00	0.00E+00	4.07E+00	0.00E+00	-3.91E-01
PERT	MJ	4.26E+03	6.69E+01	1.31E-01	6.14E+00	1.69E-01	5.35E-01
PENRE	MJ	6.35E+03	1.96E+02	1.89E+00	8.82E+00	6.75E+00	1.97E+00
PENRM	MJ	-3.93E-01	1.14E+01	0.00E+00	-1.44E-01	0.00E+00	0.00E+00
PENRT	MJ	6.35E+03	2.07E+02	1.89E+00	8.67E+00	6.75E+00	1.97E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m3	3.40E+00	1.44E-01	6.53E-05	3.98E-03	1.01E-04	1.18E-03
HWD	kg	8.73E-06	1.13E-07	7.50E-11	7.99E-08	2.45E-10	2.92E-08
NHWD	kg	8.35E+00	3.23E+00	2.54E-04	2.32E-01	6.59E-04	2.30E-02
RWD	kg	9.72E-01	5.54E-03	3.45E-06	2.47E-04	9.35E-06	4.70E-05
MFR	kg	1.57E+00	0.00E+00	0.00E+00	6.48E-02	0.00E+00	2.15E-01
MER	kg	6.31E-01	0.00E+00	0.00E+00	1.26E-01	0.00E+00	2.36E-02
EEE	MJ	1.75E+00	4.35E-02	0.00E+00	0.00E+00	0.00E+00	6.03E-02
EET	MJ	3.99E+00	7.78E-02	0.00E+00	0.00E+00	0.00E+00	9.19E-02
Biog. C in packaging	kg	1.38E+01	3.41E+00	0.00E+00	1.04E+01	0.00E+00	0.00E+00

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	D
PERE	MJ	0.00E+00	4.19E+03	1.27E-01	3.07E-01	1.24E-05	-6.90E+01
PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	0.00E+00	4.19E+03	1.27E-01	3.07E-01	1.24E-05	-6.90E+01
PENRE	MJ	0.00E+00	6.12E+03	1.68E+00	1.24E+01	6.42E-05	-1.11E+02
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	-1.16E+01	0.00E+00	0.00E+00
PENRT	MJ	0.00E+00	6.12E+03	1.68E+00	7.51E-01	6.42E-05	-1.11E+02
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.24E+00
FW	m3	0.00E+00	3.25E+00	6.25E-05	2.67E-03	1.55E-08	-4.08E-02
HWD	kg	0.00E+00	8.50E-06	6.73E-11	1.64E-09	1.40E-14	-1.08E-07
NHWD	kg	0.00E+00	4.74E+00	2.34E-04	1.15E-01	3.20E-04	-2.37E+00
RWD	kg	0.00E+00	9.66E-01	3.17E-06	4.63E-05	6.81E-10	-5.60E-03
MFR	kg	0.00E+00	0.00E+00	0.00E+00	1.29E+00	0.00E+00	0.00E+00
MER	kg	0.00E+00	0.00E+00	0.00E+00	4.81E-01	0.00E+00	0.00E+00
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	1.65E+00	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	3.82E+00	0.00E+00	0.00E+00
Biog. C in packaging	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

*Benefits and loads beyond the system boundaries

5. EXTRAPOLATION RULE FOR PRODUCT VARIANTS

5.1 Extrapolation coefficients

The extrapolation coefficients included in the PEP have been developed according to the valid PCR & PSR. The table below shows the key properties of the reference product, function as extrapolation basis.

Table 11: Reference values for the extrapolation

Export Tabelle mit textlicher Formatierung		
Parameter	Unit	Value
Weight of structural/mechanical parts	kg	1.67
Weight of power equipment	kg	0.10
Weight of light source	kg	0.002
Weight of light management system	kg	0
Weight of product (excl. packaging)	kg	1.77
Weight of packaging	kg	0.26
Typical power consumption	W	19
Lumen output	lm	2910
Energy saving coefficient	-	1.0

The extrapolation at the level of the functional unit needs to be done according to the following formula:

$$\textbf{Extrapolation coefficient at the product level} \times \left(\frac{\textbf{Lighting output of reference product (lumens)}}{\textbf{Lighting output of concerned product (lumens)}} \right)$$

The required extrapolation coefficients at the product level are listed in the following table. The Lighting output should be taken from the datasheet of the individual variant (value of phi).

Table 12: Extrapolation coefficients at the product level

Product variant	Fabrication stage	Distribution stage	Installation stage	Use stage	End of life stage
JNPL 3P L-OVL XX-XX(X) CXX ET L1,5 XX	0.95	0.95	0.89	1.00 * P (data sheet) / 19W	0.96
JNPL 3P L-OVL XX-XX(X) CXX ETDD L1,5 XX	1.02	0.99	0.89	0.50 * P (data sheet) / 19W	1.01
JNPL 3P L-OVL XX-XX(X) CXX BLE L1,5 XX	0.95	0.95	0.89	0.50 * P (data sheet) / 19W	0.95
JNPL 3P L-OVL XX-XX(X) CXX ET L3,0 XX	0.95	0.95	0.89	1.00 * P (data sheet) / 19W	0.96
JNPL 3P L-OVL XX-XX(X) CXX ETDD L3,0 XX	1.02	0.99	0.89	0.50 * P (data sheet) / 19W	1.01
JNPL 3P L-OVL XX-XX(X) CXX BLE L3,0 XX	0.95	0.95	0.89	0.50 * P (data sheet) / 19W	0.95
JNPL H20 L-OVL XX-XX(X) CXX ET L1,5 XX	1.00	1.00	1.00	1.00 * P (data sheet) / 19W	1.00
JNPL H20 L-OVL XX-XX(X) CXX ETDD L1,5 XX	1.06	1.04	1.00	0.50 * P (data sheet) / 19W	1.05
JNPL H20 L-OVL XX-XX(X) CXX BLE L1,5 XX	0.99	0.99	1.00	0.50 * P (data sheet) / 19W	0.99
JNPL H20 L-OVL XX-XX(X) CXX ET L3,0 XX	1.00	1.00	1.00	1.00 * P (data sheet) / 19W	1.05
JNPL H20 L-OVL XX-XX(X) CXX ETDD L3,0 XX	1.06	1.04	1.00	0.50 * P (data sheet) / 19W	1.05
JNPL H20 L-OVL XX-XX(X) CXX BLE L3,0 XX	1.00	1.00	1.00	0.50 * P (data sheet) / 19W	0.99

Legal Disclaimer

The information contained in this document is provided for general information purposes only and represents a standard-based environmental declaration derived from the assumptions, data and methodologies defined by the applicable standards, product category rules (PCR) and specific product rules (PSR) described herein. It does not constitute a guarantee or warranty of specific product properties, nor does it form part of any contractual agreement. The characteristics of products are binding only if expressly agreed in the relevant contract.
While TRILUX has taken reasonable care to ensure the accuracy of the data, no representation or warranty is given, either express or implied, regarding the completeness, accuracy or fitness for a particular purpose of the information provided.
The values and results stated in this EPD are valid only within the defined scope, system boundaries and assumptions. They are not intended to be used as the sole basis for environmental assessments of installations or buildings and may not be directly comparable with data from EPDs based on different standards or product category rules. TRILUX shall not be liable for any damages or consequences arising from the use or interpretation of the information contained in this document, except in cases of mandatory liability under applicable law.
Subject to technical modifications and errors.
All product names and trademarks mentioned are the property of their respective owners.