

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
T16	G5	14	827	≥ 80	-	1200	549	FDH- 14/27/1B- L/P-G5- 16/549	-	86
T16	G5	14	830	≥ 80	-	1200	549	FDH- 14/30/1B- L/P-G5- 16/549	-	86
T16	G5	14	840	≥ 80	-	1200	549	FDH- 14/40/1B- L/P-G5- 16/549	-	86
T16	G5	14	865	≥ 80	-	1100	549	FDH- 14/65/1B- L/P-G5- 16/549	-	79
T16	G5	24	827	≥ 80	-	1750	549	FDH- 24/27/1B- L/P-G5- 16/549	-	73
T16	G5	24	830	≥ 80	-	1750	549	FDH- 24/30/1B- L/P-G5- 16/549	-	73
T16	G5	24	840	≥ 80	-	1750	549	FDH- 24/40/1B- L/P-G5- 16/549	-	73
T16	G5	24	865	≥ 80	-	1600	549	FDH- 24/65/1B- L/P-G5- 16/549	-	67
T16	G5	24	940	≥ 90	-	1400	549	FDH- 24/40/1A- L/P-G5- 16/549	-	58
T16	G5	24	965	≥ 90	-	1300	549	FDH- 24/65/1A- L/P-G5- 16/549	-	54
T16	G5	21	827	≥ 80	-	1900	849	FDH- 21/27/1B- L/P-G5- 16/849	-	90
T16	G5	21	830	≥ 80	-	1900	849	FDH- 21/30/1B- L/P-G5- 16/849	-	90

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
T16	G5	21	840	≥ 80	-	1900	849	FDH- 21/40/1B- L/P-G5- 16/849	-	90
T16	G5	21	865	≥ 80	-	1750	849	FDH- 21/65/1B- L/P-G5- 16/849	-	83
T16	G5	39	827	≥ 80	-	3100	849	FDH- 39/27/1B- L/P-G5- 16/849	-	79
T16	G5	39	830	≥ 80	-	3100	849	FDH- 39/30/1B- L/P-G5- 16/849	-	79
T16	G5	39	840	≥ 80	-	3100	849	FDH- 39/40/1B- L/P-G5- 16/849	-	79
T16	G5	39	865	≥ 80	-	2850	849	FDH- 39/65/1B- L/P-G5- 16/849	-	73
T16	G5	28	827	≥ 80	-	2600	1149	FDH- 28/27/1B- L/P-G5- 16/1149	-	93
T16	G5	28	830	≥ 80	-	2600	1149	FDH- 28/30/1B- L/P-G5- 16/1149	-	93
T16	G5	28	840	≥ 80	-	2600	1149	FDH- 28/40/1B- L/P-G5- 16/1149	-	93
T16	G5	28	865	≥ 80	-	2400	1149	FDH- 28/65/1B- L/P-G5- 16/1149	-	86
T16	G5	54	827	≥ 80	-	4450	1149	FDH- 54/27/1B- L/P-G5- 16/1149	-	82
T16	G5	54	830	≥ 80	-	4450	1149	FDH- 54/30/1B- L/P-G5- 16/1149	-	82

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
T16	G5	54	840	≥ 80	-	4450	1149	FDH- 54/40/1B- L/P-G5- 16/1149	-	82
T16	G5	54	865	≥ 80	-	4050	1149	FDH- 54/65/1B- L/P-G5- 16/1149	-	75
T16	G5	54	940	≥ 90	-	3500	1149	FDH- 54/40/1A- L/P-G5- 16/1149	-	65
T16	G5	54	965	≥ 90	-	3450	1149	FDH- 54/65/1A- L/P-G5- 16/1149	-	64
T16	G5	35	827	≥ 80	-	3300	1449	FDH- 35/27/1B- L/P-G5- 16/1449	-	94
T16	G5	35	830	≥ 80	-	3300	1449	FDH- 35/30/1B- L/P-G5- 16/1449	-	94
T16	G5	35	840	≥ 80	-	3300	1449	FDH- 35/40/1B- L/P-G5- 16/1449	-	94
T16	G5	35	865	≥ 80	-	3050	1449	FDH- 35/65/1B- L/P-G5- 16/1449	-	87
T16	G5	49	827	≥ 80	-	4300	1449	FDH- 49/27/1B- L/P-G5- 16/1449	-	88
T16	G5	49	830	≥ 80	-	4300	1449	FDH- 49/30/1B- L/P-G5- 16/1449	-	88
T16	G5	49	840	≥ 80	-	4300	1449	FDH- 49/40/1B- L/P-G5- 16/1449	-	88
T16	G5	49	940	≥ 90	-	3500	1449	FDH- 49/40/1A- L/P-G5- 16/1449	-	71

Lampen- typ	Sockel	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
T16	G5	49	965	≥ 90	-	3450	1449	FDH- 49/65/1A- L/P-G5- 16/1449	-	70
T16	G5	80	827	≥ 80	-	6150	1449	FDH- 80/27/1B- L/P-G5- 16/1449	-	77
T16	G5	80	830	≥ 80	-	6150	1449	FDH- 80/30/1B- L/P-G5- 16/1449	-	77
T16	G5	80	840	≥ 80	-	6150	1449	FDH- 80/40/1B- L/P-G5- 16/1449	-	77
T16	G5	80	860	≥ 80	-	5700	1449	FDH- 80/60/1B- L/P-G5- 16/1449	-	71
T26	G13	15	827	≥ 80	950	950	438	FD- 15/27/1B- E-G13- 26/438	63	63
T26	G13	15	830	≥ 80	950	950	438	FD- 15/30/1B- E-G13- 26/438	63	63
T26	G13	15	840	≥ 80	950	950	438	FD- 15/40/1B- E-G13- 26/438	63	63
T26	G13	15	930	≥ 90	650	700	438	FD- 15/30/1A- E-G13- 26/438	43	47
T26	G13	15	954	≥ 90	680	750	438	FD- 15/54/1A- E-G13- 26/438	45	50
T26	G13	18	827	≥ 80	1350	1300	590	FD- 18/27/1B- E-G13- 26/590	75	72
T26	G13	18	830	≥ 80	1350	1300	590	FD- 18/30/1B- E-G13- 26/590	75	72

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
T26	G13	18	840	≥ 80	1350	1300	590	FD- 18/40/1B- E-G13- 26/590	75	72
T26	G13	18	865	≥ 80	1300	1250	590	FD- 18/65/1B- E-G13- 26/590	72	69
T26	G13	18	930	≥ 90	900	850	590	FD- 18/30/1A- E-G13- 26/590	50	47
T26	G13	18	940	≥ 90	950	900	590	FD- 18/40/1A- E-G13- 26/590	53	50
T26	G13	18	954	≥ 90	1000	950	590	FD- 18/54/1A- E-G13- 26/590	56	53
T26	G13	18	965	≥ 90	1000	950	590	FD- 18/65/1A- E-G13- 26/590	56	53
T26	G13	36	827	≥ 80	3350	3200	1200	FD- 36/27/1B- E-G13- 26/1200	93	89
T26	G13	36	830	≥ 80	3350	3200	1200	FD- 36/30/1B- E-G13- 26/1200	93	89
T26	G13	36	840	≥ 80	3350	3200	1200	FD- 36/40/1B- E-G13- 26/1200	93	89
T26	G13	36	865	≥ 80	3250	3150	1200	FD- 36/65/1B- E-G13- 26/1200	90	88
T26	G13	36	930	≥ 90	2200	2100	1200	FD- 36/30/1A- E-G13- 26/1200	61	58
T26	G13	36	940	≥ 90	2250	2150	1200	FD- 36/40/1A- E-G13- 26/1200	63	60

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
T26	G13	36	954	≥ 90	2300	2200	1200	FD- 36/54/1A- E-G13- 26/1200	64	61
T26	G13	36	965	≥ 90	2300	2200	1200	FD- 36/65/1A- E-G13- 26/1200	64	61
T26	G13	58	827	≥ 80	5200	5000	1500	FD- 58/27/1B- E-G13- 26/1500	90	86
T26	G13	58	830	≥ 80	5200	5000	1500	FD- 58/30/1B- E-G13- 26/1500	90	86
T26	G13	58	840	≥ 80	5200	5000	1500	FD- 58/40/1B- E-G13- 26/1500	90	86
T26	G13	58	865	≥ 80	5000	4750	1500	FD- 58/65/1B- E-G13- 26/1500	86	82
T26	G13	58	930	≥ 90	3500	3400	1500	FD- 58/30/1A- E-G13- 26/1500	60	59
T26	G13	58	940	≥ 90	3600	3500	1500	FD- 58/40/1A- E-G13- 26/1500	62	60
T26	G13	58	954	≥ 90	3700	3600	1500	FD- 58/54/1A- E-G13- 26/1500	64	62
T26	G13	58	965	≥ 90	3700	3600	1500	FD- 58/65/1A- E-G13- 26/1500	64	62
T-R16	2GX13	22	827	≥ 80	-	1800	230	FC- 22/27/1B- E- 2GX13- 16	-	82
T-R16	2GX13	22	830	≥ 80	-	1800	230	FC- 22/30/1B- E-	-	82

Lampen- typ	Sockel	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								2GX13- 16		
T-R16	2GX13	22	840	≥ 80	-	1800	230	FC- 22/40/1B- E- 2GX13- 16	-	82
T-R16	2GX13	22	865	≥ 80	-	1700	230	FC- 22/65/1B- E- 2GX13- 16	-	77
T-R16	2GX13	40	827	≥ 80	-	3200	305	FC- 40/27/1B- E- 2GX13- 16	-	80
T-R16	2GX13	40	830	≥ 80	-	3200	305	FC- 40/30/1B- E- 2GX13- 16	-	80
T-R16	2GX13	40	840	≥ 80	-	3200	305	FC- 40/40/1B- E- 2GX13- 16	-	80
T-R16	2GX13	40	865	≥ 80	-	3000	305	FC- 40/65/1B- E- 2GX13- 16	-	75
T-R16	2GX13	55	827	≥ 80	-	4200	305	FC- 55/27/1B- E- 2GX13- 16	-	76
T-R16	2GX13	55	830	≥ 80	-	4200	305	FC- 55/30/1B- E- 2GX13- 16	-	76
T-R16	2GX13	55	840	≥ 80	-	4200	305	FC- 55/40/1B- E- 2GX13- 16	-	76
T-R16	2GX13	55	865	≥ 80	-	3800	305	FC-	-	69

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								55/65/1B- E- 2GX13- 16		
TC-SEL	2G7	5	827	≥ 80	-	250	85	FSD- 5/27/1B- E-2G7	-	50
TC-SEL	2G7	5	840	≥ 80	-	250	85	FSD- 5/40/1B- E-2G7	-	50
TC-SEL	2G7	7	827	≥ 80	-	400	115	FSD- 7/27/1B- E-2G7	-	57
TC-SEL	2G7	7	830	≥ 80	-	400	115	FSD- 7/30/1B- E-2G7	-	57
TC-SEL	2G7	7	840	≥ 80	-	400	115	FSD- 7/40/1B- E-2G7	-	57
TC-SEL	2G7	9	827	≥ 80	-	600	145	FSD- 9/27/1B- E-2G7	-	67
TC-SEL	2G7	9	830	≥ 80	-	600	145	FSD- 9/30/1B- E-2G7	-	67
TC-SEL	2G7	9	840	≥ 80	-	600	145	FSD- 9/40/1B- E-2G7	-	67
TC-SEL	2G7	11	827	≥ 80	-	900	215	FSD- 11/27/1B- E-2G7	-	82
TC-SEL	2G7	11	830	≥ 80	-	900	215	FSD- 11/30/1B- E-2G7	-	82
TC-SEL	2G7	11	840	≥ 80	-	900	215	FSD- 11/40/1B- E-2G7	-	82
TC-L	2G11	18	827	≥ 80	1200	1200	225	FSD- 18/27/1B- E-2G11	67	67
TC-L	2G11	18	830	≥ 80	1200	1200	225	FSD- 18/30/1B- E-2G11	67	67
TC-L	2G11	18	840	≥ 80	1200	1200	225	FSD- 18/40/1B- E-2G11	67	67
TC-L	2G11	18	930	≥ 90	750	750	225	FSD- 18/30/1A-	42	42

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								2G11		
TC-L	2G11	18	940	≥ 90	750	750	225	FSD- 18/40/1A- 2G11	42	42
TC-L	2G11	18	950	≥ 90	750	750	225	FSD- 18/50/1A- 2G11	42	42
TC-L	2G11	24	827	≥ 80	1800	1800	320	FSD- 24/27/1B- E-2G11	75	75
TC-L	2G11	24	830	≥ 80	1800	1800	320	FSD- 24/30/1B- E-2G11	75	75
TC-L	2G11	24	840	≥ 80	1800	1800	320	FSD- 24/40/1B- E-2G11	75	75
TC-L	2G11	24	930	≥ 90	1200	1200	320	FSD- 24/30/1A- 2G11	50	50
TC-L	2G11	24	940	≥ 90	1200	1200	320	FSD- 24/40/1A- 2G11	50	50
TC-L	2G11	24	950	≥ 90	1200	1200	320	FSD- 24/50/1A- 2G11	50	50
TC-L	2G11	36	827	≥ 80	2900	2900	415	FSD- 36/27/1B- E-2G11	81	81
TC-L	2G11	36	830	≥ 80	2900	2900	415	FSD- 36/30/1B- E-2G11	81	81
TC-L	2G11	36	840	≥ 80	2900	2900	415	FSD- 36/40/1B- E-2G11	81	81
TC-L	2G11	36	860	≥ 80	2750	2750	415	FSD- 36/60/1B- E-2G11	76	76
TC-L	2G11	36	930	≥ 90	1900	1900	415	FSD- 36/30/1A- 2G11	53	53
TC-L	2G11	36	940	≥ 90	1900	1900	415	FSD- 36/40/1A- 2G11	53	53
TC-L	2G11	36	950	≥ 90	1900	1900	415	FSD- 36/50/1A- 2G11	53	53
TC-L	2G11	40	827	≥ 80	-	3500	535	FSDH- 40/27/1B-	-	88

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								2G11		
TC-L	2G11	40	830	≥ 80	-	3500	535	FSDH- 40/30/1B- 2G11	-	88
TC-L	2G11	40	840	≥ 80	-	3500	535	FSDH- 40/40/1B- 2G11	-	88
TC-L	2G11	40	950	≥ 90	-	2200	535	FSDH- 40/50/1A- 2G11	-	55
TC-L	2G11	55	827	≥ 80	-	4800	535	FSDH- 55/27/1B- 2G11	-	87
TC-L	2G11	55	830	≥ 80	-	4800	535	FSDH- 55/30/1B- 2G11	-	87
TC-L	2G11	55	840	≥ 80	-	4800	535	FSDH- 55/40/1B- 2G11	-	87
TC-L	2G11	55	860	≥ 80	-	4550	535	FSDH- 55/60/1B- 2G11	-	83
TC-L	2G11	55	930	≥ 90	-	3000	535	FSDH- 55/30/1A- 2G11	-	55
TC-L	2G11	55	940	≥ 90	-	3000	535	FSDH- 55/40/1A- 2G11	-	55
TC-L	2G11	55	950	≥ 90	-	3000	535	FSDH- 55/50/1A- 2G11	-	55
TC-L	2G11	80	830	≥ 80	-	6000	565	FSDH- 80/30/1B- 2G11	-	75
TC-L	2G11	80	840	≥ 80	-	6000	565	FSDH- 80/40/1B- 2G11	-	75
TC-D	G24d- 1	10	827	≥ 80	600	-	95	FSQ- 10/27/1B- I-G24d=1	60	-
TC-D	G24d- 1	10	830	≥ 80	600	-	95	FSQ- 10/30/1B- I-G24d=1	60	-
TC-D	G24d- 1	10	840	≥ 80	600	-	95	FSQ- 10/40/1B- I-G24d=1	60	-
TC-D	G24d- 1	13	827	≥ 80	900	-	130	FSQ- 13/27/1B-	69	-

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								I-G24d=1		
TC-D	G24d- 1	13	830	≥ 80	900	-	130	FSQ- 13/30/1B- I-G24d=1	69	-
TC-D	G24d- 1	13	840	≥ 80	900	-	130	FSQ- 13/40/1B- I-G24d=1	69	-
TC-D	G24d- 2	18	827	≥ 80	1200	-	140	FSQ- 18/27/1B- I-G24d=2	67	-
TC-D	G24d- 2	18	830	≥ 80	1200	-	140	FSQ- 18/30/1B- I-G24d=2	67	-
TC-D	G24d- 2	18	840	≥ 80	1200	-	140	FSQ- 18/40/1B- I-G24d=2	67	-
TC-D	G24d- 3	26	827	≥ 80	1800	-	160	FSQ- 26/27/1B- I-G24d=3	69	-
TC-D	G24d- 3	26	830	≥ 80	1800	-	160	FSQ- 26/30/1B- I-G24d=3	69	-
TC-D	G24d- 3	26	840	≥ 80	1800	-	160	FSQ- 26/40/1B- I-G24d=3	69	-
TC-DEL	G24q- 1	10	827	≥ 80	-	600	95	FSQ- 10/27/1B- E- G24q=1	-	60
TC-DEL	G24q- 1	10	830	≥ 80	-	600	95	FSQ- 10/30/1B- E- G24q=1	-	60
TC-DEL	G24q- 1	10	840	≥ 80	-	600	95	FSQ- 10/40/1B- E- G24q=1	-	60
TC-DEL	G24q- 1	13	827	≥ 80	-	900	130	FSQ- 13/27/1B- E- G24q=1	-	69
TC-DEL	G24q- 1	13	830	≥ 80	-	900	130	FSQ- 13/30/1B- E- G24q=1	-	69
TC-DEL	G24q- 1	13	840	≥ 80	-	900	130	FSQ- 13/40/1B- E-	-	69

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								G24q=1		
TC-DEL	G24q- 2	18	827	≥ 80	-	1200	140	FSQ- 18/27/1B- E- G24q=2	-	67
TC-DEL	G24q- 2	18	830	≥ 80	-	1200	140	FSQ- 18/30/1B- E- G24q=2	-	67
TC-DEL	G24q- 2	18	840	≥ 80	-	1200	140	FSQ- 18/40/1B- E- G24q=2	-	67
TC-DEL	G24q- 3	26	827	≥ 80	-	1800	160	FSQ- 26/27/1B- E- G24q=3	-	69
TC-DEL	G24q- 3	26	830	≥ 80	-	1800	160	FSQ- 26/30/1B- E- G24q=3	-	69
TC-DEL	G24q- 3	26	840	≥ 80	-	1800	160	FSQ- 26/40/1B- E- G24q=3	-	69
TC-T	G24d- 1	13	827	≥ 80	900	-	90	FSM- 13/27/1B- I-G24d=1	69	-
TC-T	G24d- 1	13	830	≥ 80	900	-	90	FSM- 13/30/1B- I-G24d=1	69	-
TC-T	G24d- 1	13	840	≥ 80	900	-	90	FSM- 13/40/1B- I-G24d=1	69	-
TC-T	G24d- 2	18	827	≥ 80	1200	-	100	FSM- 18/27/1B- I-G24d=2	67	-
TC-T	G24d- 2	18	830	≥ 80	1200	-	100	FSM- 18/30/1B- I-G24d=2	67	-
TC-T	G24d- 2	18	840	≥ 80	1200	-	100	FSM- 18/40/1B- I-G24d=2	67	-
TC-T	G24d- 3	26	827	≥ 80	1800	-	115	FSM- 26/27/1B- I-G24d=3	69	-
TC-T	G24d- 3	26	830	≥ 80	1800	-	115	FSM- 26/30/1B-	69	-

Lampen- typ	Socket	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								I-G24d=3		
TC-T	G24d-3	26	840	≥ 80	1800	-	115	FSM- 26/40/1B- I-G24d=3	69	-
TC-TEL	G24q-1	13	827	≥ 80	-	900	90	FSMH- 13/27/1B- E-G24q-1	-	69
TC-TEL	G24q-1	13	830	≥ 80	-	900	90	FSMH- 13/30/1B- E-G24q-1	-	69
TC-TEL	G24q-1	13	840	≥ 80	-	900	90	FSMH- 13/40/1B- E-G24q-1	-	69
TC-TEL	G24q-2	18	827	≥ 80	-	1200	100	FSMH- 18/27/1B- E-G24q-2	-	67
TC-TEL	G24q-2	18	830	≥ 80	-	1200	100	FSMH- 18/30/1B- E-G24q-2	-	67
TC-TEL	G24q-2	18	840	≥ 80	-	1200	100	FSMH- 18/40/1B- E-G24q-2	-	67
TC-TEL	G24q-3	26	827	≥ 80	-	1800	115	FSMH- 26/27/1B- E-G24q-3	-	69
TC-TEL	G24q-3	26	830	≥ 80	-	1800	115	FSMH- 26/30/1B- E-G24q-3	-	69
TC-TEL	G24q-3	26	840	≥ 80	-	1800	115	FSMH- 26/40/1B- E-G24q-3	-	69
TC-TEL	G24q-3	32	827	≥ 80	-	2400	130	FSMH- 32/27/1B- E-G24q-3	-	75
TC-TEL	G24q-3	32	830	≥ 80	-	2400	130	FSMH- 32/30/1B- E-G24q-3	-	75
TC-TEL	G24q-3	32	840	≥ 80	-	2400	130	FSMH- 32/40/1B- E-G24q-3	-	75
TC-TEL	G24q-4	42	827	≥ 80	-	3200	155	FSMH- 42/27/1B- E-G24q-4	-	76
TC-TEL	G24q-4	42	830	≥ 80	-	3200	155	FSMH- 42/30/1B- E-G24q-4	-	76
TC-TEL	G24q-4	42	840	≥ 80	-	3200	155	FSMH- 42/40/1B-	-	76

Lampen- typ	Sockel	Lampen- leistung (W)	Licht- farbe	Farb- wieder- gabe- Index Ra	Lampen- Nenn- lichtstrom am VVG (lm)	Lampen- Nenn- lichtstrom am EVG (lm)	Lampen- länge bzw. Ring- durch- messer (mm)	ILCOS- Code	Lampen- Licht- ausbeute am VVG (lm/W)	Lampen- Licht- ausbeute am EVG (lm/W)
								E-G24q-4		
TC-F	2G8	24	827	≥ 80	1700	1700	165	FSS- 24/27/1B- E-2G8	71	71
TC-F	2G8	24	830	≥ 80	1700	1700	165	FSS- 24/30/1B- E-2G8	71	71
TC-F	2G8	24	840	≥ 80	1700	1700	165	FSS- 24/40/1B- E-2G8	71	71
TC-F	2G8	36	827	≥ 80	2800	2800	217	FSS- 36/27/1B- E-2G8	78	78
TC-F	2G8	36	830	≥ 80	2800	2800	217	FSS- 36/30/1B- E-2G8	78	78
TC-F	2G8	36	840	≥ 80	2800	2800	217	FSS- 36/40/1B- E-2G8	78	78